



FEEL THE SW DIFFERENCE®

DURABILITY THAT'S ON CALL FOR THE TOUGHEST OF JOBS.

MegaMan®

MM-11BK
POWDER-FREE ECOTEK BIODEGRADABLE EXAMINATION GLOVES WITH MOISTURE-WICKING DRITEK TECHNOLOGY

SWEAT MANAGEMENT AND ANSI LEVEL 3 ABRASION RESISTANCE FOR THE ULTIMATE IN COMFORT AND PERFORMANCE

- DriTek® Comfort Technology with absorbent lining wicks away moisture for all day comfort
- EcoTek® Biodegradability Technology accelerates landfill breakdown without any performance loss*
- ANSI/EN Level 3 abrasion resistance for durability and extended wear
- Fully textured surface for excellent grip
- 1.5 AQL exceeds laboratory standards
- Up to 3x longer lasting than standard nitrile gloves
- SHA Dermatologically Approved



ANSI/EN level 3 abrasion resistance


Fully textured surface for wet and dry grip

Tear-resistant beaded cuff for easy donning

MM **MM-11BK**

WEIGHT	LENGTH	THICKNESS	FEATURES	COLOR
12.8g (large size)	11"	8.5 mil	DriTek® EcoTek®	BLACK

ECOTEK



SW®
33278 Central Avenue, Unit 102, Union City, CA 94587, USA
Tel: +1.510.429.8692 | Fax: +1.510.487.5347
Trademarks and registered trademarks are the property of SW and its affiliates.
©2022 SW. All rights reserved.



TECHNICAL DATA



MM-11BK
POWDER-FREE ECOTEK BIODEGRADABLE
EXAMINATION GLOVES WITH MOISTURE-
WICKING DRITEK TECHNOLOGY



PRODUCT DESCRIPTION

SPECIFICATIONS

PRODUCT	MegaMan®
GRADE	Powder-Free Exam
MATERIAL	Nitrile
THICKNESS FINGER	10.1mil 0.26mm
PALM	8.5mil 0.22mm
CUFF	7.0mil 0.18mm
COLOR	Black
SURFACE OUTER	Fully Textured
INNER	DriTek®
LENGTH	11" 280mm
WEIGHT	12.8g
FIT TYPE	Ambidextrous
CUFF TYPE	Beaded
WATERTIGHT AQL	1.5
ORIGIN COUNTRY	China

PHYSICAL PROPERTIES

	PRE-AGING	POST-AGING
TENSILE STRENGTH:	17 MPa	16 MPa
ELONGATION:	560%	520%

INTEGRATED TECHNOLOGIES

DRITEK Comfort Technology:
 Advanced flock lining is a powder-free, soft cotton nitrile glove lining that wicks away moisture for added comfort in extended use.

ECOTEK Biodegradability Technology: 92.6% biodegradable in 2.5 years. ASTM D5526-12 test results do not predict future biodegradation.*

100% Air Inspected

* Specifications based on size Large glove

STANDARDS & CERTIFICATIONS

EN ISO 21420:2020
 EN 455-2000-2015
 ASTM D6319-19
 ASTM D6978-05 (2019)
 ASTM F1671-13
 ASTM F739-12
 Reach EU 1907/2006

EU 2016/425
 ANSI/ISEA 105-2016
 CAT III Complex Design
 FDA 21 CFR 177.2600



Please visit swsafety.com/symbols for information on standards used on this document.

ORDERING

ITEM NO.	SIZE	PALM WIDTH	PACKAGING
N260881	XS 5½ – 6	3.0" 76mm	50 gloves per box 10 boxes per case
N260882	S 6½ – 7	3.4" 87mm	50 gloves per box 10 boxes per case
N260883	M 7½ – 8	3.8" 97mm	50 gloves per box 10 boxes per case
N260884	L 8½ – 9	4.3" 109mm	50 gloves per box 10 boxes per case
N260885	XL 9½ – 10	4.5" 114mm	50 gloves per box 10 boxes per case
N260886	2XL 10½ – 11	4.9" 125mm	50 gloves per box 10 boxes per case
N260887	3XL 11½ – 12	5.3" 134mm	50 gloves per box 10 boxes per case

APPLICATIONS

INDUSTRIAL

- Assembly
- Fabrication
- Janitorial Maintenance
- Light Machining Operations
- Maintenance
- Waste Management

MEDICAL

- Chemical Handling
- First Responder EMS
- Tattooing and Cosmetic Procedures

Keep out of sunlight. Store in a cool, dry place.
 Keep away from sources of ozone or ignition.



R_N26088X1121



SW®
 33278 Central Avenue, Unit 102, Union City, CA 94587, USA
 Tel: +1.510.429.8692 | Fax: +1.510.487.5347
 Trademarks and registered trademarks are the property of SW and its affiliates.
 ©2022 SW. All rights reserved.



*Under test method ASTM D5526-12, a standard test method for determining anaerobic biodegradation of plastics in accelerated landfill conditions. Current biodegradation results do not predict future results.