i-SENSYS, LBP710Cx LBP712Cx

High- capacity, fast colour printers for busy workgroups.

Fast colour laser printers packed into a compact footprint. These high-capacity printers are ideal for demanding workplaces.



Fast and flexible printing

- Colour A4 printing at either 33 ppm (LBP710Cx) or 38 ppm (LBP712Cx)
- Colour A5 printing at either 55 ppm (LBP710Cx)¹ or 59 ppm (LBP712Cx)¹
- Ideal for busy working environments that demand a reliable, versatile printer.
- The ability to have up to 4 high-capacity paper feeder cassettes (*only available on LBP712Cx)

High-capacity in a small footprint

- Large 650-page capacity as standard, expandable to 2,300 pages (*only LBP712Cx).
- A compact and capable office companion, this larger capacity still comes in a small package.
- Built for versatility, from A5 to A4 double-sided documents, they are ready to deliver in seconds.

Working on the go

- Support for Apple AirPrint (iOS) and Mopria (Android), you can print easily from any compatible device.
- Benefit from more advanced features with the Canon PRINT Business mobile app.
- Google Cloud print-ready for seamless integration.

Higher capacity toner cartridges

- The toner seal inside the cartridge is now automatically removed when the cartridge is fitted, cutting down on waste and installation time.
- In the same compact size, the new Genuine Canon toner cartridges now have a higher capacity, letting you be even more productive.

Canon's exceptional image quality

- These devices produce superior colour graphics, images and text in laser quality prints to make a greater impact on the reader.
- Canon's renowned image expertise ensures that businesses of any size can produce professional looking documents

Smart networking capabilities

- Support for PCL5e/6 and Adobe PostScript printer languages enable hassle-free integration into managed network
- The devices are equally well-suited to managed print service environments and are compatible with Canon's e-Maintenance remote service management system.
- The LBP710 series can also be integrated into Canon's uniFLOW output management platform, bringing you the efficiency and security of My Print Anywhere plus the added benefits of accounting and cost recovery.





Optional Accessories

i-sensys, LBP710Cx LBP712Cx

Paper Feeder PF- D1

• Additional 550 sheet paper cassette. LBP710Cx : 1 in total can be added to main unit LBP712Cx : 3 in total can be added to main unit

Plain Pedestal- P1

• Place under the device to increase height when free standing

Barcode Printing Kit-F1

• Installs bar code fonts for bar code printing. This kit, which is delivered boxed, includes a license access certificate for activation.

SD Card- C1

• 8GB SD card memory for various functions such as print job spooling, encrypted secured print, secured print, and electronic sort.

PCL Font Set- C1

• Unicode printing capability on SAP and supports Andale font.

i-SENSYS LBP710Cx LBP712Cx



Main unit



Санон

Canon	
	intre.
	Ľ
	<u> </u>
	E
	T.

Main unit + 1 Paper Feeder- D1 2

Main unit + 2 Paper Feeders- D1 (LBP712Cx only)

Main unit + 3 Paper Feeders- D1 (LBP712Cx only)



Technical Specifications

i-SENSYS, LBP710Cx LBP712Cx

Sound power³ Active: 65/66 dB (LBP710Cx / LBP712Cx) Standby: 50/51 dB (LBP710Cx / LBP712Cx)

PRINTER ENGINE

Print speed

Printing method Print quality Print resolution Warm-up time First Page Out Time

Recommended Monthly Print Volume Duty cycle Print margins

Advanced printing features

MEDIA HANDLING

Paper input (Standard)

Paper input (Option)

Paper output Media types

Media sizes

Media weights

Double sided printing

GENERAL FEATURES

Power requirements Power consumption Single sided (A4): Up to 33/38 ppm colour and mono (LBP7IOCx/LBP7I2Cx) Double sided (A4): Up to 33/38 ipm colour and mono (LBP7IOCx/LBP7I2Cx) Single sided (A5 - Landscape) : Up to 55/59 ppm colour and mono (LBP7IOCx/LBP7I2Cx) Colour laser beam printing Up to 9600 x 600 dpi Up to 600 x 600 dpi Approx. 31 seconds or less from power on Colour: approx. 6.0 seconds Mono; approx. 5.1 seconds 2,000 - 6,000 pages per month (LBP7IOCx) 2,000 - 7,500 pages per month (LBP7IOCx)

2,000 - 7,500 pages per month (I Max. 80,000 pages per month¹ 5 mm-top, bottom, left and right

Secure Print Print from USB memory key (JPEG / TIFF / PDF) Barcode Print² Google Cloud Print Ready IOS: AirPrint, Canon PRINT Business app Android; Mopria certified, Canon Print Service Plug-in, Canon PRINT Business app

550-sheet cassette 100-sheet multi-purpose tray

550-sheet cassette x 1 (LBP710Cx) 550-sheet cassette x 3 (LBP712Cx) 200-sheet face down

Plain paper, Recycled paper, Heavy Paper, Colour paper, Label, Envelope, Post card, Rough paper Cassette (Standard):

Cassette (Standard): A4, B5, A5, A5 (Landscape), LTR, EXE, STMT, K16 Custom size - width: 101.6 to 215.9 mm, length: 148 to 297 mm

Multi-purpose tray: A4, B5, A5, A5 (Landscape), A6, LGL, LTR, EXE, FLS, K16, STMT, Index card (3"x5") Custom size - width: 76.2 to 215.9 mm, length: 127 to 355.6 mm

Cassette (Optional): A4, B5, A5, A5 (Landscape), LGL, LTR, EXE, STMT, FLS, K16 Custom size - width: 101.6 to 215.9 mm, length: 148 to 355.6 mm

Cassette: 60 to 163 g/m² Multi-purpose tray: 60 to 216 g/m²

Automatic Cassette (Standard and optional): A4, B5, A5, LGL, LTR, EXE, FLS, K16 Custom size - width: 148 to 215.9 mm, length: 210 to 355.6 mm 60 to 163 g/m²

220-240V (310%) 50/60Hz (32Hz)

Maximum: Approx. 1470W or less Active: Approx.570W/590W or less (LBP710Cx / LBP712Cx) Standby: Approx. 34W or less Sleep: Approx. 1.3W or less Power switch off: 0.16W or less Typical Electricity Consumption (TEC): 1.4kWh/week Idle time required to enter sleep mode: 1-180 min (default: 1 min) Idle time required to enter Auto Shutdown: 4 hours (default) Noise level

Sound pressure³ Active: 51 dB Standby: 37/36 dB (LBP710Cx/LBP712Cx) Dimensions (W x D x H) 458 mm x 464 mm x 388 mm Approx, 28.8 kg Weight Temperature: 10 to 30°C (50 to 86°F) Humidity 20 to 80% RH (no condensation) Operating environment 5 Line LCD, 5 LED (Online, Ready, Message, Job and Energy saver), Control panel Buttons, 10-key numeric keypad CONTROLLER 528MHz + 264 MHz **Processor Speed** Memorv 1GB UFRII (Ultra Fast Rendering), PCL5c⁴, PCL⁶, Adobe® PostScript Printer Languages Fonts 93 PCL fonts, 136 PS fonts USB 2.0 High-Speed, 10BASE-T/100 BASE-TX/1000BASE-T

Interface and connectivity Software and Printer Management

Operating Systems Compatibility

CONSUMABLES

All-in-One cartridges

ACCESSORIES/OPTIONS

Standard: Cartridge 040 Black (6,300 pages⁶)⁹ Cartridge 040 Cyan (5,400 pages⁶)⁷ Cartridge 040 Magenta (5,400 pages⁶)⁷ Cartridge 040 Vellow (5,400 pages⁶)⁹ High yield:

Remote User Interface (RUI).

Server® 2003 Mac OS X version 10.6.8 & up Linux⁵/Citrix

SFP MEAP

High yield: Cartridge 040H Black (12,500 pages⁶)⁷ Cartridge 040H Cyan (10,000 pages⁶)⁷ Cartridge 040H Magenta (10,000 pages⁶)⁷ Cartridge 040H Yellow (10,000 pages⁶)⁷ Waste Toner Box: WT-B1 (approx. 54,000 A4 pages)

Paper Feeder PF-DI (550-sheet cassette) SD CARD-CI (8GB SD card memory) Barcode Printing Kit-F1 (Enables barcode printing capability) PCL Font Set-CI (Enables Unicode printing capability on SAP and supports Andale font) MICard Multi (Card reader for identification with RFID or magnetic cards with uniFLOW) Micard Plus (Card reader for identification with RFID or magnetic cards with uniFLOW) Plain Pedestal-P1

Nemote Oser Interface (NOI), Department ID Management, Toner Status Tool, IW Management Console: Server-based software for centralised management of a fleet of devices eMaintenance: embedded RDS allows remote eMaintenance services such as meter capture, automatic consumables management and remote diagnostics. uniFLOW compatibility with uniFLOW Login Device Client for

Windows* 10 / Windows* 8.1 / Windows* 8 / Windows* 7 / Windows* Vista / Server* 2012R2 / Server* 2012 / Server* 2008R2 / Server* 2008 / Server* 2003R2 /

Footnotes

⁽¹⁾ Duty cycle is defined as the maximum number of printed pages for a single peak month. Any usage above the recommended duty cycle may decrease the life of the product

^[2] Accessory - Barcode Printing Kit-F1 - is required

^[3] Declared noise emission in accordance with ISO 9296
^[4] Commands supported only. Third party driver or direct printing from application required

^[5] Web distribution only. Driver will be available in October, 2016

^[6] Based on ISO/IEC 19798

^[7] Printer ships with Cartridge 040

Canon Inc. canon.com Canon Europe canon-europe.com English edition © Canon Europa N.V.,2016



High- capacity, fast colour printers for busy workgroups.

i-sensys, LBP710Cx LBP712Cx

Fast colour laser printers packed into a compact footprint. These high-capacity printers are ideal for demanding workplaces.

Sales Start Date: July 2016



Product Details:

Product Name	Mercury Code	EAN Code
i-SENSYS LBP710Cx EUR	0656C006AA	4549292059397
i-SENSYS LBP712Cx EUR	0656C001AA	4549292041033

Optional Accessories:

Product Name	Mercury Code	EAN Code
Paper Feeder PF-D1	0942C001AA	4549292050714
PCL Font Set-C1	0643A029AA	4549292048605
SD Card-C1	0655A004AA	4549292051452
Barcode Printing Kit-F1	0660A018AA	4960999689562
Plain Pedestal Type-P1	1632C001AA	8714574633756
Waste Toner Box WT-B1	0942C002AA	4549292052688

Consumables:

Product Name	Mercury Code	EAN Code
Cartridge 040 Black	0460C001AA	4549292058239
Cartridge 040 Cyan	0458C001AA	4549292058222
Cartridge 040 Magenta	0456C001AA	4549292058215
Cartridge 040 Yellow	0454C001AA	4549292058208
Cartridge 040 H Black	0461C001AA	4549292058277
Cartridge 040 H Cyan	0459C001AA	4549292058260
Cartridge 040 H Magenta	0457C001AA	4549292058253
Cartridge 040 H Yellow	0455C001AA	4549292058246

Measurement / Logistic Information:

Product Name	Mercury code	Package Style	Quantity per pack	Length (mm)	Width (mm)	Height (mm)	Weight (kg)
i-SENSYS LBP710CX EUR 0656C006AA i-SENSYS LBP712CX EUR 0656C001AA		Box	1	602	602	531	35
	OUSOCOURA	Pallet	4	656	1267	1065	140
	-	Container 40ft HCD	216	-	-	-	-

What's in the box?

- Main unit
- Canon Cartridge 040
- Power supply cable
- Starter Guide
- User Software DVD-ROM
- Warranty card

