



TECHNICAL PRODUCT DATASHEET









UPDATED: 28/02/2019

Kutlass® PU500G

High cut resistant green liner with flexible PU palm coating.

A specialised blend of advanced yarns provide cut level 5 protection in a lightweight, highly versatile glove. The incorporation of spandex vastly increases comfort and fit. Flexible PU coating provides superb dexterity and grip. The breathable liner reduces perspiration and works in conjunction with the Sanitized® hygiene functionto provide a fresh, comfortable and odour free experience throughout extended usage.



FEATURES AND TECHNOLOGY

















MANUFACTURING



STEEL & METAL



WASTE & RECYCLING



GLASS



TYPICAL INDUSTRIES

BUILDING & CONSTRUCTION

TECHNICAL INFORMATION

ORDER REF#	G/KUTLAS/PU500G	
COATING MATERIAL	PU	
PACKING	PER PACK: 5	PER CASE: 50
SIZES AVAILABLE	7 (S), 8 (M), 9 (L), 10 (XL), 11 (2XL)	
EU TYPE CERTIFICATION BY	SATRA Technology Europe Ltd, Bracetown Business Park, Clonee, Dublin, D15 YN2P, Ireland (Notified Body No. 2777)	

CERTIFICATION AND STANDARDS (SEE OVERLEAF FOR FURTHER DETAILS)




¹ 'X' denotes not tested. ² * Where applicable, EN388:2016 scores take precedent and are

ongoing. $^{\rm 3}$ There is no correlation between coupe test levels and EN ISO 13997 / TDM cut test levels.









Fax: +44 (0)1902 451 271

Email: sales@ultimateindustrial.co.uk

Web: www.ultimateindustrial.co.uk



Registered in England No. 2035621



TECHNICAL PRODUCT DATASHEET







COLOUR CODED



UPDATED: 28/02/2019

CERTIFICATION LEGENDS





> 5

NEWTON


≥ 30 ≥ 22 ≥ 15

≥ 10

LEVEL

D

С











EN511:2006







* For details regarding user exposure, see

FURTHER INFORMATION

STORAGE/TRANSPORT: Keep away from direct sunlight; store in a cool dry place. Keep away from ozone sources or naked flame. Store the gloves in their original packaging. During transportation, ensure the product is well packaged and protected in order to prevent any damage.

PRECAUTIONS BEFORE USE: 1. Never use these gloves with chemicals. 2. Gloves should not be used when there is a risk of entanglement with moving machine parts. 3. Before usage and periodically during usage, inspect the gloves for any defects or imperfections. Avoid wearing damaged, dirty or worn out gloves. 4. The gloves should not come in contact with a naked flame or fire. 5. Do not subject to high speed or serrated blades. 6. Always read enclosed user instructions before using these gloves. 7. Whilst these gloves are highly cut resistant, they are not cut proof. 8. The information provided is for products in a new condition and does not reflect the actual duration of protection in the workplace. 9. Service life cannot be specified and depends on the application and the responsibility of the user to ascertain suitability of the glove for its intended use

CONSTITUENTS / ALLERGIES: Some gloves may contain ingredients which are known to be a possible cause of allergies in sensitive persons who may develop irritant and/or allergic contact reactions. If an allergic reaction should occur seek medical advice immediately. This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.

*SANITIZED® TREATMENT


Sanitized®: These gloves incorporate a Biocidal product. The Biocidal treatment protects against a broad spectrum of Bacteria and Fungi. The active Biocidal substance - Zinc Pyrithione - promotes freshness and inhibits odours.




For more information about this product, or to access the Declaration of Conformity or Product Certification, visit; https://www.ultimateindustrial.co.uk/product/692-Kutlass-PU500G

If appropriate to the product, EC/EU Declaration of Conformities, relevant certification and supporting documentation are available to access through your distributor, at the above web address(s) or by contacting UCi customer services quoting the product reference code. This document and any other statement provided herein by or on behalf of UCi are given for informational purposes and do not constitute a contractual agreement nor warranty of merchantability. UCi assumes no responsibility for the suitability or adequacy of an end user's selection of product for a specific purpose. The manufacturer reserves the right to make any modifications it deems necessary. All product and company names are trademarks of their respective holders. © UCi Limited, 2019













¹Testing carried out on the palm material. Except in cases where the glove is equal to or over 400mm - where the cuff is tested also tested. ² 'X' denotes Not Tested. ³ Where applicable, EN388:2016 scores take precedent and are ongoing. There is no correlation between coupe test levels and ISO 13997 / TDM cut test levels. Where both EN388:2016 and EN388:2003 scores are shown, the latter is shown for informational purposes only.