



VISITOR

Clear Polycarbonate



FRAME

- Wraparound polycarbonate frame
- Integrated side shields and orbital protection
- Economic over-spec for visitors
- Can be worn over prescription glasses
- Weight : 27 g.

LENS

- Clear polycarbonate lens
- Optical quality class 1
- 100% UV filtration (in conformity with EN 170)
- Resistance to impact (45m/s)
- Visible Light Transmittance = 92%

FIELDS OF USE

- Mechanical hazards (marking F - 45m/s)
 - solid particles projectiles (metal, wood...) riveting, drilling...
- UV radiation

DO NOT USE FOR

Does not protect against liquid, dust, laser beam molten metal, or any kind of welding application.

FRAME MARKING

AOS EN166 - F CE

AOS = manufacturer AOSafety
EN166 = n° of the standard
F = low impact resistance (45m/s)
CE = conformity marking

EUROPEAN STANDARD

This product conforms to the European Council Directive 89/686/EEC and with the EN166 :1995

EC-Type Examination Certificate n° 826

Issued by Inspec Certification Ltd (0194)
Upper Wingbury Courtyard, Wingrave, Aylesbury
Buckinghamshire, HP22LW, England

Conform to EN166 - EN170

LENS MARKING

2-1,2 . AOS . 1 . F

2 = UV filter (in conformity with EN 170)
1,2 = shade number (clear lens)
AOS = manufacturer AOSafety
1 = optical class (permanent wear)
F = low impact resistance (45m/s)

PRODUCT REFERENCE

Product Code	Frame	Lens	Material
71448-00001C	Std		PC

