

Product data sheet folding mask FFP3 - uvex silv-Air 3310



UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, 90766 Fürth, Germany

Product features	<ul style="list-style-type: none"> • Optimised shape • Soft material edges for high wearing comfort • The adjustable head band clips offer easy handling and comfortable fit • Exhalation valve for reduced build-up of heat and moisture inside the mask • Flexible and adjustable nosepiece • Mask fulfils the requirements of the dolomite dust test (D) • Compatible with uvex safety eyewear
Materials	<p>Head band: elastic textile Nose piece: PP Headband clips: PP Filter / mask: Melt Blown PP, Polyester Sealing lip: EVA foam Valve: ABS</p>

Areas of use The respiratory protection mask can be used against solid, aqueous and non-volatile liquid aerosols up to 30 times the respective limit values.	Welding, soldering, high concentrations of very hazardous and microscopic respirable dust and with chemical compounds that contain beryllium, stibium, arsenic, cadmium, cobalt, nickel, platinum, radium or strychnine.
Weight	17 g
Standard	EN 149:2001 + A1:2009

Versions/Colour:

Artkle-No.	Colour/Version	Retail unit
8733.310	Folding mask FFP3, white with valve	15 pieces per box