NLNW-D 13 Gauge Nylon Glove

Product Datasheet

OUR REF: NLNW-D

PRODUCT DESCRIPTION

Low linting 13 gauge Nylon shell to minimise contamination of products. Soft, seamless construction for wearer comfort in a range of sizes to ensure a secure, snug fit. PVC dotting to palm and PVC fingertips to improve grip and durability. Good dexterity across a wide range of applications.

TYPICAL APPLICATIONS

Light general handling, assembly, Specialist handling operations, Inspection.

AVAILABLE SIZES: 7/s • 8/m • 9/L • 10/xL

PACKAGING: Per Pack: 10 pairs

Per Box: 240 pairs




Technical Details

Tested in accordance with EN 388, EC type examination carried out by:

SATRA Quality Assurance Ltd, SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom (Notified Body No. 0321)

The results are taken from the palm area of the gloves Abrasion and the un-coated surface may have reduced performance levels.



- Storage: Gloves should be stored in a cool, dry environment in the original packaging and out of direct sunlight.
- Maintenance: Both new and old gloves should be thoroughly inspected before use to ensure no damage is present. Gloves should not be left in a contaminated condition if reuse is intended if contaminated, gloves should be cleaned as far as possible

For more information contact:

T: +44 (0) 1902 451 451 **F:** +44 (0) 1902 451 276 **E:** sales@ultimateindustrial.co.uk

www.ultimateindustrial.co.uk

Ultimate Industrial Limited

Victoria House, Colliery Road, Wolverhampton, WV1 2RD United Kingdom

