



## TEGERA® 10PG

Chemical protection glove, PVC (Vinyl), interlock, cotton, smooth finish, Cat. III, red, oil and grease resistant, for heavy work

### PROPERTIES

Very durable

### SPECIFICATION

TYPE OF GLOVE Disposable and/or chemical resistant gloves

CATEGORY Cat. III

SIZE RANGE (EU) 8, 9, 10, 11

LINER MATERIAL Interlock, cotton

DIPPING MATERIAL PVC (Vinyl)

DEXTERITY 5

GRIP PATTERN Smooth finish

LENGTH RANGE 350 mm

COLOUR Red

PAIRS PER PACKAGE/CARTON 12/60

AQL 0.65

OUTER MATERIAL SPECIFICATION Polyvinyl chloride

INNER MATERIAL SPECIFICATION Cotton

ANTIBACTERIAL/BIOCIDAL TREATMENT] Pyrithione zinc (CAS number 13463-41-7)

SIZE	ART. NO.	EAN NO.
10	10pg-10	7392626001084
8	10pg-8	7340118310626
9	10pg-9	7392626062702
11	10pg-11	7340118310619

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

## TEGERA® 10PG

### FEATURES

Protection against chemicals

### PRIMARY PROTECTION

Prevents risk of, corrosive injuries, contact with moisture, contact with oil and fat

### PRIMARY ENVIRONMENTS OF USE

Chemical risk environments, microbiological risk environments, environments hazardous to health, corrosive environments, wet environments, moist environments, oil and greasy environments, harsh environments

### PRIMARY AREAS OF USE

Building and construction, HVAC installation, construction, soil preparation, concrete work, mining, agricultural work, marine work, petro-chemical work, chemical work, chemical technology work, paper industry work, decontamination, sanitation

### PRIMARY INDUSTRIES OF USE


Agriculture, mining, oil, gas, petrochemical, pulp and paper, chemical, rubber and plastic, metal fabrication

### TYPE OF WORK

Heavy weight



CE 0120 Cat. III



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2016-12-30

2(4)

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10


info@ejendals.com

order@ejendals.com

www.ejendals.com



CE 0120 Cat. III



## TEGERA® 10PG

### EC TYPE EXAMINATION

Notified Body: 0120 SGS United Kingdom, Unit 202B Worle Parkway, Weston-super-Mare, BS22 6WA, United Kingdom

### CHEMICAL RESISTANCE

According to EN 374-3. For details, please contact Ejendals

### COMPLIANCE DESCRIPTION

EN 420:2003 Protective gloves - general requirements and test methods

EN 388:2003 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
A) Resistance to wear (No. of revolutions)	4	(4)
B) Resistance to cutting (Index)	1	(5)
C) Tear resistance (Newton)	2	(4)
D) Puncturing resistance (Newton)	1	(4)

EN 388 - Testing (specifies the requirements that apply for each safety level).

Level of protection	1	2	3	4	5
A) Resistance to wear (No. of revolutions)	100	500	2000	8000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	

EN 374-2:2003 Protective gloves against chemicals and micro-organisms - Part 2: Determination of resistance to penetration

EN 374-3:2003 Protective gloves against chemicals and micro-organisms - Part 3: Determination of resistance to permeation by chemicals

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.



## TEGERA® 10PG

Permeation levels are based on breakthrough times as follows

Permeation level	1	2	3	4	5	6
Minimum breakthrough times (min)	10	30	60	120	240	480

Definition of breakthrough time through the glove palm (1ugm/cm<sup>2</sup>/min)

A: Methanol (CAS Number 67-56-1) - Permeation level 2

K: Sodium hydroxide 40% (CAS number 1310-73-2) - Permeation level 6

L: Sulphuric acid 96% (CAS number 7664-93-9) - Permeation level 3

**CE** 0120 Cat. III

 EN 388:2003  
4121

 EN 374-2

 EN 374-3  
AKL



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2016-12-30

4(4)

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com