

## iiyama ProLite XUB2493HS-B6 - LED monitor - Full HD (1080p) - 24"(XUB2493HS-B6)

iiyama ProLite XUB2493HS-B6 - LED monitor - 24" (23.8" viewable) - 1920 x 1080 Full HD (1080p) @ 100 Hz - IPS - 250 cd/m<sup>2</sup> - 1300:1 - 0.5 ms - HDMI, DisplayPort - speakers - black, matte



### Main Specifications

Product Description	iiyama ProLite XUB2493HS-B6 - LED monitor - Full HD (1080p) - 24"
Device Type	LED-backlit LCD monitor - 24"
Energy Label QR Code URL	<a href="https://eprel.ec.europa.eu/qr/1873044">https://eprel.ec.europa.eu/qr/1873044</a>
Energy Class	Class E
Power Consumption (On mode)	16 W
Panel Type	IPS
Native Resolution	Full HD (1080p) 1920 x 1080 at 100 Hz
Pixel Pitch	0.275 mm
Brightness	250 cd/m <sup>2</sup>
Contrast Ratio	1300:1 / 80000000:1 (dynamic)
Response Time	0.5 ms (MPRT)
Colour Support	16.7 million colours
Colour Gamut	72% NTSC, 96% sRGB
Input Connectors	HDMI, DisplayPort
Display Position Adjustments	Height, pivot (rotation), swivel, tilt
Screen Coating	Matte
Voltage	AC 100-240 V (50/60 Hz)
Colour	Black, matte
Dimensions (WxDxH) - with stand (lowest position)	53.95 cm x 20.95 cm x 34.3 cm
Weight	5.1 kg
Environmental Standards	TCO Certified Displays 9
Compliant Standards	DDC-2B, DDC/CI, RoHS, WEEE, PSE Mark, REACH, TUV Bauart, ERP, VCCI Class B, EAC, REACH SvHC, UKCA

### Extended Specification

#### General

Display Type	LED-backlit LCD monitor / TFT active matrix
Energy Label QR Code URL	<a href="https://eprel.ec.europa.eu/qr/1873044">https://eprel.ec.europa.eu/qr/1873044</a>

Energy Class	Class E
Diagonal Size	24"
Viewable Size	23.8"
Panel Type	IPS
Native Resolution	Full HD (1080p) 1920 x 1080 at 100 Hz
Pixel Pitch	0.275 mm
Brightness	250 cd/m <sup>2</sup>
Contrast Ratio	1300:1 / 80000000:1 (dynamic)
Colour Support	16.7 million colours
Colour Gamut	72% NTSC, 96% sRGB
Response Time	0.5 ms (MPRT)
Vertical Refresh Rate	48 - 100 Hz
Horizontal Refresh Rate	30 - 115 kHz
Horizontal Viewing Angle	+89 / -89
Vertical Viewing Angle	+89 / -89
Screen Coating	Matte
Backlight Technology	LED backlight
OSD Languages	Czech, English, German, French, Italian, Polish, Russian, Dutch, Japanese
Features	HDCP, Overdrive technology, Advanced Contrast Ratio (ACR), X-Res Technology, Flicker Free technology, Motion Blur Reduction, Adaptive-Sync technology, Blue Light Reducer Function, Eco Mode, 3-sided borderless, i-Style colour
Colour	Black, matte
Dimensions (WxDxH)	53.95 cm x 20.95 cm x 34.3 cm - with stand (lowest position)
Weight	5.1 kg

#### Miscellaneous

Features	Security lock slot (cable lock sold separately), VESA interface support, cable management system
Cables Included	1 x HDMI cable
Compliant Standards	DDC-2B, DDC/CI, RoHS, WEEE, PSE Mark, REACH, TUV Bauart, ERP, VCCI Class B, EAC, REACH SvHC, UKCA
Security Slot Type	Kensington security slot

#### Power

Input Voltage	AC 100-240 V (50/60 Hz)
Power Consumption (On mode)	16 W
Power Consumption SDR (On mode)	16 kWh/1000h
Power Consumption (Typical)	16 Watt
Power Consumption Stand by	0.5 Watt
Power Consumption (Off Mode)	0.3 Watt

#### Environmental Parameters

Min Operating Temperature	5 °C
Max Operating Temperature	35 °C
Humidity Range Operating	10 - 90% (non-condensing)

#### Audio

Type	Speakers - stereo
Output Power / Channel	2 Watt

#### Connectivity

Interfaces	HDMI   DisplayPort   Headphones
------------	---------------------------------

## Dimensions & Weight

Dimensions & Weight Details	With stand (lowest position) - width: 53.95 cm - depth: 20.95 cm - height: 34.3 cm - weight: 5.1 kg   With stand (highest position) - width: 53.95 cm - depth: 20.95 cm - height: 49.3 cm - weight: 5.1 kg   Without stand - width: 53.95 cm - depth: 3.9 cm - height: 32.55 cm
-----------------------------	---

## Mechanical

Display Position Adjustments	Height, pivot (rotation), swivel, tilt
Tilt Angle	-5/+23
Swivel Angle	90
Rotation Angle	90
Height Adjustment	150 mm
VESA Mounting Interface	100 x 100 mm

## Sustainability Information

TCO Certified	TCO Certified Displays 9
---------------	--------------------------

## What's in the box

iiyama ProLite XUB2493HS-B6  
HDMI cable

\*TD SYNEX is not responsible for errors in the documentation of products.