



## TEGERA® 517

Synthetic leather glove, winter-lined, 0,7 mm synthetic leather, polyester, fleece, Cat. II, black, green, chrome free, Velcro®, for precision work

### PROPERTIES

Good fingertip sensitivity, flexible, good grip, good fit, comfortable

### SPECIFICATION

TYPE OF GLOVE Cold insulation gloves

CATEGORY Cat. II

SIZE RANGE (EU) 8, 9, 10, 11

PALM MATERIAL Synthetic leather

PALM THICKNESS 0,7 mm

BACK MATERIAL Polyester

LINING Winter-lined

LINING MATERIAL Fleece

DEXTERITY 3

FASTENING Velcro®

LENGTH RANGE 235-255 mm

COLOUR Black, green

PAIRS PER PACKAGE/CARTON 6/60

DISPLAY Hook with hangtag

OUTER MATERIAL SPECIFICATION Polyurethane, polyester, natural latex

MIDDLE MATERIAL SPECIFICATION Polyethylene

INNER MATERIAL SPECIFICATION Polyester

AQUATHAN®



SIZE	ART. NO.	EAN NO.
8	517-8	7392626070745
9	517-9	7392626070769
10	517-10	7392626070707
11	517-11	7392626070721

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

## TEGERA® 517

### FEATURES

Chrome free, reinforced index finger, reinforced fingertips, windproof, short model, waterproof

### PRIMARY PROTECTION

Prevents risk of: chrome allergy, abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt, drying out, chapping, contact with moisture, contact with damp, contact with cold

### PRIMARY ENVIRONMENTS OF USE

Windy environments, slippery environments, dry environments, cold environments, wet environments, moist environments, oil and greasy environments, dirty environments

### PRIMARY AREAS OF USE

Assembly, machine operating, building and construction, carpentry, installation work, HVAC installation, construction, soil preparation, engineering, transport work, machine driving, warehouse work, airport work

### PRIMARY INDUSTRIES OF USE

Automotive, transportation, utilities, logistics, HoReCa, facilities, service, retail

### TYPE OF WORK

Light weight

 Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2017-05-26

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

[info@ejendals.com](mailto:info@ejendals.com)

[order@ejendals.com](mailto:order@ejendals.com)

[www.ejendals.com](http://www.ejendals.com)

## TEGERA® 517

### EC TYPE EXAMINATION

Notified Body: 0321 SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom

### COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EN 388:2003 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
A) Resistance to abrasion (No. of revolutions)	1	(4)
B) Resistance to cutting (Index)	1	(5)
C) Tear resistance (Newton)	2	(4)
D) Puncturing resistance (Newton)	1	(4)

EN 388 - Testing (specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
A) Resistance to abrasion (No. of revolutions)	100	500	2000	8000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	

EN 511:2006 Protective gloves against cold



CE Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2017-05-26

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com