



LG-88

Product Reference	Low-Cut Lace-Up Shoes
Specifications	MS ISO 20345:2008
Sizes	UK #3 - #13
Weight (s.41)	± 600 g
Height	4 inches



Model description:

Durable shoes with an impact protection of 200 Joules and penetration protection of 1100 Newtons, pierce-resistant steel midsole insert, and an extra light, slip-resistant polyurethane (PU) sole that is resistant to oil, acid & alkalis.

Application areas:

Warehousing Industry, Logistics Industry, Construction Industry, Manufacturing Industry, etc.

Precaution and maintenance of the shoe:

We recommend to protect them and clean them regularly with appropriate cleaning products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description
Steel Toe Cap	Provide protection against falling objects up to 200J.
Steel Midsole	Designed to protect from sharp objects entering underfoot.
Upper	Durable to keep feet comfortable at all times.
Lining	Padded, moisture-wicking and highly breathable.
Outsole	Single-density PU sole, lightweight, flexible, stylish comfort combined with reliable foot protection against slipping, twisting and joint pain. Shock absorbent, abrasion resistant and resistant to mineral oils and weak acids.
Insole	Anti-fatigue, good shock absorption for walking, comfort and work safety.