



■ TEGERA® 134



[Learn more](#)

SUPERIOR FOR WELDING AND CUT PROTECTION

Superior welding and cut protection glove for heavy-duty jobs. Thin full grain goat suede provides excellent tactility. KEVLAR® liner inside the glove for extra heat and cut protection. Specially treated leather for work in slightly wet and oily applications. Elasticated wrist for better fit. KEVLAR® seams and black colour for added durability and extended product life. The back of the hand is reinforced with NOMEX®.

CHARACTERISTICS

- High level of protection
- Good fingertip sensitivity
- Durable
- Good fit

FUNCTIONS

- Withstands contact heat up to 100°C
- Extra long
- Reinforced index finger
- Reinforced seams
- Water and oil repellent
- Withstands welding sparks and grinding splash

Kevlar®

PREVENTS RISK OF

Burn injuries, Heat injuries, Cut injuries, Abrasion injuries, Blisters, Grazes, Scratches, lacerations, Contact with dirt, Contact with damp

PRIMARY ENVIRONMENTS OF USE

Cut risk environments, Warm environments, Moist environments, Oily and greasy environments, Harsh environments

PRIMARY AREAS OF USE

Metalwork, Welding, Hot work, Sheet-metal work

PRIMARY INDUSTRIES OF USE

Automotive, Metal fabrication, Machinery and equipment, MRO

TYPE OF WORK

Medium weight

SPECIFICATION

TYPE Cut resistant gloves, Heat protection gloves, Welding gloves

CATEGORY Cat. III

PALM MATERIAL Heat-resistant and water-repellent premium reversed goat suede

BACK MATERIAL Heat-resistant and water-repellent premium reversed goat suede

LINING Fully lined

LINING MATERIAL KEVLAR® fiber, Nomex®

LENGTH 395 mm

DEXTERITY 3

COLOUR Brown

PAIRS PER: BUNDLE/CARTON 6/60

DISPLAY TYPE Thread

FASTENING Elasticated 180°

CUFF STYLE Extended safety cuff

CUFF MATERIAL Leather

CUT RESISTANCE (EN ISO 13997) Cut resistance level C

CUT RESISTANCE (EN ISO 13997) TDM: 10.8 N

INNER MATERIAL SPECIFICATION Para-aramid

MIDDLE MATERIAL SPECIFICATION Meta-aramid

OUTER MATERIAL SPECIFICATION Leather

COMPLIANCE



TP TC 019:2011

EN ISO 21420:2020



EN 388:2016+A1:2018 3X22C



EN 407:2020 41334X

EN 12477:2001+A1:2005

Type A

EN 1149-2:1997 R > 1,0 x10⁶ Ω



Warning, this model is not intended for use in wet conditions

FEATURES



Cut protection



Water repellent

SIZE		ARTICLE NUMBER	EAN
10	XL	134-10	7392626040632
11	XXL	134-11	7392626040649
7	S	134-7	7392626060326
8	M	134-8	7392626060333
9	L	134-9	7392626040625

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden

Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com