

M52015-WH
M52015S-WH

OP AIR-PRO® OXYGEN
RESPIRATORY PROTECTION MASK FFP2 NR D
Personal Protective Equipment, Category III

FEATURES & BENEFITS

- Filtering half mask, efficiency class FFP2 NR D developed to protect against solid and liquid aerosols
- Ultrasonic welding
- M52015S items are individually packed in a polybag

Recommended use :

- Use in dusty environment
- To prevent against risky infectious diseases (According to national recommendations)
- Using: 8 H



PRODUCT DETAILS

| | |
|--------------------|--|
| Product name: | KOLMI - Op-Air Pro® Oxygen – Mask FFP2 NR D |
| Product type: | Single use, non-sterile |
| Inner/Outer layer: | Spunbond 100% polypropylene |
| Filter: | Meltblown 100% polypropylene |
| Nosepiece: | Polypropylene and iron |
| Color : | White |
| Origin : | France |



EN 149:2001+A1:2009

| Test | Required level | Laboratory | Report number | Date of Report | Average value |
|---------------------------------------|---|------------|---------------|----------------|---------------|
| Paraffin Oil penetration | < 6 % after 120mg exposure | APAVE | 20.1742 | 01/12/2020 | Compliant |
| NaCl penetration | < 6 % after 120mg exposure | | | | Compliant |
| Facial leakage | ≤ 11 % for at least 46 results over 50 ≤ 8% for at least 8 arithmetic means over 10 | | | | Compliant |
| Air permeability inhalation 30 l/min | ≤ 0,7 mbars | | | | Compliant |
| Air permeability inhalation 95 l/min | ≤ 2,4 mbars | | | | Compliant |
| Air permeability exhalation 160 l/min | ≤ 3 mbars | | | | Compliant |
| Carbon dioxide content | < 1,0 % | | | | Compliant |
| Flammability | Must not burn or continue to burn for more than 5 seconds after the withdrawal of the flame | | | | Compliant |

Protection (D) : protection against solid and liquid aerosols, combined with resistance higher to clogging tested with dolomite dust

Annual observation according to module D - Reg (UE) 2016/425 done by APAVE

CERTIFICATION & STANDARDS

Meet the requirements of Regulation (EU) 2016/425 on personal protective equipment.
Comply with the applicable harmonized standards EN 149:2001+A1:2009.
Manufactured under ISO 13485 and ISO 9001 certified systems.

PRECAUTIONS FOR USE

The device should only be used on intact skin.
Their re-use or prolonged use can produce infection or cross-contamination.
After use, comply with the national regulations in force for the disposal of the device.

STORAGE

Normal conditions of conservation and storage: must not be exposed to humidity and sun, must be stored at a temperature between 5°C and 40°C.
Product life: 5 years.

LOGISTICAL INFORMATION



Outer case specifications

| Item | Size mm | Gross weight kg | QTY/pallet |
|-------------------------|-----------------|-----------------|-----------------------------------|
| M52015-WH M52015S-WH | 560 x 260 x 270 | To be confirmed | 36 boxes (6 layers of 6 boxes) |

Inner case specifications

| Size mm | QTY |
|-----------------|--------------------------|
| 255 x 110 x 133 | 10 boxes of 50 pieces |

M52015S-WH items are individually packed in a polybag.

Codes EAN

| Article | Carton | Boîte distributrice |
|------------|-------------------|---------------------|
| M52015-WH | 3 662 036 018 670 | 3 662 036 018 663 |
| M52015S-WH | 3 662 036 018 694 | 3 662 036 018 687 |