Fax: 0049-(0)7223-284-245



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.06.2015 Version number 9 Revision: 18.06.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: UHU The All Purpose Adhesive
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesives
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier: UHU GmbH & Co.KG Herrmannstraße 7 D-77815 Bühl (Baden) Tel.:0049-(0)7223-284-0 email: info @uhu.boltongroup.de

· Further information obtainable from: CRD

• 1.4 Emergency telephone number: Tel.: +49 (0) 72 23/28 40

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



GHS02

- · Signal word Danger
- · Hazard statements

H225 Highly flammable liquid and vapour.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

ENG



Printing date 18.06.2015 Version number 9 Revision: 18.06.2015

Trade name: UHU The All Purpose Adhesive

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Adhesive

· Dangerous components:		
CAS: 79-20-9 EINECS: 201-185-2	methyl acetate Tam. Liq. 2, H225; Eye Irrit. 2, H319; STOT	50-80%
Reg.nr.: 01-2119459211-47-XXXX CAS: 64-17-5	SE 3, H336 ethanol	5,0-<10%
	♦ Flam. Liq. 2, H225	5,0-<10%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-XXXX 02-2119752542-40-0000	acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	5,0-<10%

· Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures
 Ensure adequate ventilation
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Pick up mechanically.

Send for recovery or disposal in suitable receptacles.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

(Contd. on page 3)



Printing date 18.06.2015 Version number 9 Revision: 18.06.2015

Trade name: UHU The All Purpose Adhesive

(Contd. of page 2)

See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:					
79-20-9 methyl a	79-20-9 methyl acetate				
AGW (Germany)	Long-term value: 610 mg/m³, 200 ppm 4(II);DFG, Y				
64-17-5 ethanol	64-17-5 ethanol				
AGW (Germany)	Long-term value: 960 mg/m³, 500 ppm 2(II);DFG, Y				
67-64-1 acetone	67-64-1 acetone				
IOELV (EU)	Long-term value: 1210 mg/m³, 500 ppm				
AGW (Germany)	Long-term value: 1200 mg/m³, 500 ppm 2(I);Y, DFG, EU, AGS				
· Ingredients with	· Ingredients with biological limit values:				
67-64-1 acetone	67-64-1 acetone				
BGW (Germany)	80 mg/l Untersuchungsmaterial: Urin Probennahmezeitpunkt: Expositionsende bzw. Schichtende Parameter: Aceton				

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid direct contact with the chemical/ the product/ the preparation by organisational measures.

- · Respiratory protection: Not required.
- · Protection of hands:

Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 4)



Printing date 18.06.2015 Version number 9 Revision: 18.06.2015

Trade name: UHU The All Purpose Adhesive

(Contd. of page 3)

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Not required.

SECTION 9: Physical and ch	lemical properties			
9.1 Information on basic physical and chemical properties				
General Information				
· Appearance: Form:	Fluid			
Colour:	Colourless			
· Odour:	Characteristic			
· Odour threshold:	Not determined.			
· pH-value:	Not determined.			
Change in condition				
Melting point/Melting range:	Undetermined.			
Boiling point/Boiling range:	55 °C			
· Flash point:	-13 °C			
Flammability (solid, gaseous):	Not applicable.			
· Ignition temperature:	425 °C			
· Decomposition temperature:	Not determined.			
· Self-igniting:	Product is not selfigniting.			
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.			
· Explosion limits:				
Lower:	3,1 Vol %			
Upper:	16,0 Vol %			
· Vapour pressure at 20 °C:	220 hPa			
· Density at 20 °C:	0,99 g/cm ³			
· Relative density	Not determined.			
· Vapour density	Not determined.			
· Evaporation rate	Not determined.			
· Solubility in / Miscibility with				
water:	Not miscible or difficult to mix.			
· Partition coefficient (n-octanol/wa	ter): Not determined.			
· Viscosity:				
Dynamic at 20 °C:	4400 mPas			
Kinematic:	Not determined.			
· Solvent content:				
Organic solvents:	65,9 %			
Water:	0,4 %			
VOC (EC)	65,85 %			

(Contd. on page 5)



Printing date 18.06.2015 Version number 9 Revision: 18.06.2015

Trade name: UHU The All Purpose Adhesive

(Contd. of page 4)

Solids content: 33,8 %

• 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

	· · · · · · · · · · · · · · · · · · ·					
	· LD/LC50 values relevant for classification:					
ſ	79-20-9 methyl acetate					
	Oral	LD50	3705 mg/kg (rabbit)			
Ī	64-17-5 ethanol					
	Oral	LD50	7060 mg/kg (rat)			
	Inhalative	LC50/4 h	20000 mg/l (rat)			
	67-64-1 acetone					
	Oral	LD50	5800 mg/kg (rat)			
	Dermal	LD50	20000 mg/kg (rabbit)			

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow product to reach ground water, water course or sewage system.

- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.

(Contd. on page 6)



Printing date 18.06.2015 Version number 9 Revision: 18.06.2015

Trade name: UHU The All Purpose Adhesive

(Contd. of page 5)

· vPvB: Not applicable.

• 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

· European waste catalogue

08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14. Transport inform	SECTION 14: Transport information		
14.1 UN-Number ADR, IMDG, IATA	UN1133		
14.2 UN proper shipping name ADR	1133 ADHESIVES, special provision 640H 1133 KLEBSTOFFE, Sondervorschrift 640H		
IMDG, IATA	ADHESIVES		
14.3 Transport hazard class(es)			
ADR, IMDG, IATA			
Class Label	3 Flammable liquids. 3		
14.4 Packing group			
ADR IMDG, IATA	III II		
14.5 Environmental hazards: Marine pollutant:	No		
14.6 Special precautions for user	Warning: Flammable liquids.		
Danger code (Kemler): EMS Number:	-		
	F-E,S-D		
14.7 Transport in bulk according to A of Marpol and the IBC Code	I nnex II Not applicable.		
Transport/Additional information:			

ENG



Printing date 18.06.2015 Version number 9 Revision: 18.06.2015

Trade name: UHU The All Purpose Adhesive

	(Contd. of page 6
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	E
· IMDG	
· Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN1133, ADHESIVES, special provision 640H, 3,

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Department issuing MSDS: CRD

· Contact:

Frau A. Liar,

Herr Dr. C. Hanf

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

· * Data compared to the previous version altered.