

Material datasheet

Product		Adress Labels white
SAP Code 2433		
Material description		Woodfree, white machine finished paper The paper is FSC certified mixed credit
Printer suitability		Ink jet, laser, copier, flexography, letterpress, offset and screenprint
Thickness		91 µm
Grammage		70 g/m²
Adhesive		
Description		Acrylic, water based adhesive
Performance		Special designed product for office documentation, address labelling, logistics and industrial applications. The adhesive complies with the European food regulations and regulations. It can be used for the labelling of food packaging .
Bonding		Universal permanent adhesive for A4 application.
Liner		
Description		white kraft paper wood free
Thickness		54 μm
Grammage		51 g/m²
Laminate		
Thickness		148 μm
Grammage		144 g/m²
Service temperature		- 20 °C / + 100 °C no negative influence with a short-time higher temperature e.g. during printing on a laser printer
Min. application temperature		5°C
Opt. storage conditions		20°C and 50 % RH
Shelf life		From the date of manufacture 4 years as opt. storage conditions
Physical parameter		
Whiteness (CIE) %	ISO 11475	164
Opacity (%)	ISO 2471	92
Packaging		
Material		100-sheet-pack F Flute recycled, 430 g/m ² 25-shett-pack: GD2 Recycled, 400 g/m ²
Recycling		
Face / liner		All components use environment friendly components. The liner is neutral, does not contain dangerous or water contaminating components and can be added to the paper recycling process
Packaging		Recyclable
		·

N.B.: All data to be considered as typical values