

# Safety data sheet for chemical products

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: UB-157 Blue [ uni-ball eye fine ]

Manufacture's name : MITSUBISHI PENCIL CO.,LTD.  
 Address : 5-23-37, HIGASHIOHI, SHINAGAWA, TOKYO, JAPAN  
 Telephone number : 03-3458-6281 Telefax number : 03-3450-0363  
 Telex number : 2422337 MBPENC J.

Creation Date : May 7, 2001  
 Revision Date : September 30, 2011  
 File No. : 066122A Rev. 2.5.03.03

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

The chemical product is a substance or a preparation : Preparation

Chemical nature: Component parts : Ink

Chemical or generic name	CAS No.	TSCA	EINECSNo.	Concentration range (wt%)
Water	7732-18-5	Registered	2317912	50- 80
Glycerine	56-81-5	Registered	2002895	< 10
1,2-Propanediol	57-55-6	Registered	2003380	< 10
Diethylene glycol	111-46-6	Registered	2038722	< 10
Coloring agent	Registered	Registered	Registered	< 10
Resin	Registered	Registered	Polymer	< 10

Other parts : Other parts are excluded from 'chemical substances'.

## 3. HAZARDS IDENTIFICATION

Most important hazards : Not available.

Specific hazards : Not available.

## 4. FIRST-AID MEASURES

Inhalation:

Not applicable.

(Due to its low vapor pressure. Inhalation is unlikely at room temperature.)

Skin contact:

Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention, if needed. Thoroughly clean and dry contaminated clothing and shoes before reuse.

Eye contact:

Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.

Ingestion:

If swallowed, seek medical advice, and show the MSDS to the physician then.

[Ink quantity of product : about 2.1g]

---

## 5. FIRE-FIGHTING MEASURES

---

Fire and explosion measures : Slight fire hazard.

Extinguishing media:

- Suitable : regular dry chemical, carbon dioxide, water, regular foam.
- Large fires : Use regular foam or flood with fine water spray.
- Fire fighting : Move container from fire area if it can be done without risk.  
Use extinguishing agents appropriate for surrounding fire.  
Avoid inhalation of material or combustion by-products.  
Stay upwind and keep out of low areas.

---

## 6. ACCIDENTAL RELEASE MEASURES

---

- Personal precautions : Not available.
- Environmental precautions : Do not wash away into shower or water way.
- Methods for cleaning up : Wipe off by dry cloth and wash with water.  
: In accordance with national, state and local regulations.

---

## 7. HANDLING AND STORAGE

---

Store and handle in accordance with all current regulations and standards.

Keep separated from incompatible substances.

Handling:

- Technical measures : Don't swallow ink.  
: Recap after use.  
: Don't shake.  
: Keep out of the reach of children.  
: Avoid contact with skin and eyes.
- Precautions : Not available.
- Safe handling advice : Not available.

Storage:

- Technical measures : Keep away from oxidizing materials, ignition sources and high temperature.
- Storage condition : Avoid direct sunlight.  
: Do not leave the products in high temperature space.  
: Recommended temperature: 0-30 C.
- Incompatible products : (Information of components.)
 

acids, bases, oxidizing materials, metal oxides, peroxides, reducing agents	Glycerine
acids, bases, combustible materials, halo carbons, metals, metal salts, oxidizing materials, reducing agents	1,2-Propanediol
acids, bases, oxidizing materials	Diethylene glycol
oxidizing materials	Coloring agent / Resin
- Packaging materials : Not applicable.

---

## 8. EXPOSURE CONTROL / PERSONAL PROTECTION

---

Engineering measures : Not required.

Control parameters (Information of components.)

OSHA	5mg/m <sup>3</sup> TWA(respirable dust fraction), 15mg/m <sup>3</sup> TWA(total dust) 5mg/m <sup>3</sup> (Respirable flaction), 15mg/m <sup>3</sup> (Total dust) [Nuisance Dust]	Glycerine Coloring agent
ACGIH	10mg/m <sup>3</sup> TWA 10mg/m <sup>3</sup> (Nuisance particulate)	Glycerine Coloring agent
EC	Not available.	
DFG	44 mg/m <sup>3</sup> (10ml/m <sup>3</sup> ) MAK(peak limitation category-II, 2)	Diethylene glycol
UK	150ppm(474mg/m <sup>3</sup> ) TWA(total(vapor and pariclutates)), 10mg/m <sup>3</sup> TWA(particlutates)	1,2-Propanediol

Personal protective equipment : Not required.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

[ ] : Information of components.

Physical state and form	: Low viscous liquid.
Colour	: Blue.
Odour	: None odour.
pH	: 8.5±0.5
Boiling point	: Not available. [Water/ 100 C]
Melting point	: <-10 C
Flash point	: Not applicable. [1,2-Propanediol/ 99 C]
Autoignition temperature	: Not applicable. [Diethylene glycol/ 224 C]
Explosion limits	: Not applicable. [ Lower flammable limit / 0.026% , Upper flammable limit / 0.125% <1,2-Propanediol> ]
Density	: about 1.1 / 25 C
Vapour density (air=1)	: Not available. [1,2-Propanediol/ 2.60-2.62]
Solubility in water	: Soluble.
Evaporation rate	: Not available.
Volatile	: 88-91%

---

## 10. STABILITY AND REACTIVITY

---

Stability : Stability.

Hazardous reactions : Will not occur.

Conditions to avoid : Avoid heat, flames, sparks and other sources of ignition.  
Avoid contact with incompatible materials.

Materials to avoid : (Information of components.)

acids, bases, oxidizing materials, metal oxides, peroxides, reducing agents	Glycerine
acids, bases, combustible materials, halo carbons, metals, metal salts, oxidizing materials, reducing agents	1,2-Propanediol
acids, bases, oxidizing materials	Diethylene glycol
oxidizing materials	Coloring agent / Resin

Hazardous decomposition products	: (Information of components.)
oxides of carbon, water	common decomposition products
corrosive acrolein.	Glycerine
oxides of nitrogen.	Coloring agent

---

## 11. TOXICOLOGICAL INFORMATION

---

(Information of components)

Acute toxicity

Ingestion LD50	4090mg/kg-Mouse 20000mg/kg-Rat 3300mg/kg-Cat, 7800mg/kg-Guinea pig ≥5000mg/kg-Rat	Glycerine 1,2-Propanediol Diethylene glycol  Coloring agent
Inhalation LC50	>570mg/m <sup>3</sup> -1H-Rat	Glycerine
Skin LD50	>10000mg/kg-Rabbit 20800mg/kg-Rabbit 11890mg/kg-Rabbit	Glycerine 1,2-Propanediol Diethylene glycol

Local effects                      Irritant:skin                      Diethylene glycol

Chronic toxicity and long term toxicity

Repeated or prolonged contact may cause skin sensitization.                      1,2-Propanediol

Signs and Symptoms of overexposure and aggravated by exposure

Inhalation	irritation,difficulty breathing nausea,headache nausea,cough irritation	Glycerine 1,2-Propanediol Diethylene glycol Coloring agent / Resin
Skin contact	irritation,redness irritation,allergic reaction irritation	Glycerine / Diethylene glycol 1,2-Propanediol Resin
Eye contact	tearing,stinging irritation,pain irritation,redness irritation	Glycerine 1,2-Propanediol Diethylene glycol Coloring agent / Resin
Ingestion	nausea,vomiting allergic reaction,vomiting gastric disturbances	Glycerine / Diethylene glycol 1,2-Propanediol Coloring agent

Specific effects                      Not available.

---

## 12. ECOLOGICAL INFORMATION

---

Not available.

---

## 13. DISPOSAL CONSIDERATIONS

---

Waste from residues                      : Disposal in accordance with all current regulations and standards.

Contaminated packaging : Not applicable.

---

## 14. TRANSPORT INFORMATION

---

HS Code : 960810

---

## 15. REGULATORY INFORMATION

---

### Regulations (Information of components)

Hazardous chemicals (OSHA HCS) : Glycerine

### EU labeling

25<=Xn;R22 : Diethylene glycol

R22 : Harmful if swallowed.

### CANADA Hazardous Products Act - Ingredient Disclosure List

1%over : 1,2-Propanediol

### Hazard and safety information

Products are manufactured in accordance with ISO 8124-3 " Safety of Toys - Part 3"

---

## 16. OTHER INFORMATION

---

This sheet completes the technical sheet of use but it doesn't replace it.

The information contained in this sheet are based knowledge of the products at the data : (September 30, 2011). They are given quite sincerely.

Moreover the attention of the users is drawn on the risks possibly taken, when a product is used for other utilization than these which it is intended.