greenly

2025-09-17

Lyreco LCA

Life Cycle Assessment


The methodology in this report is based on ISO 14040

12953229 (sold in TH)

Summary



01 Methodology



02 Results





Methodology

Environmental Impact Assessment

Functional unit

The functional unit is a quantified performance of a product system for use as a reference unit. One of the primary purposes of a functional unit is to provide a reference to which the input and output data are normalized (in a mathematical sense).

The functional unit of this analysis is "6 set(s) of bound pages of paper for the purpose of writing".

Impact Indicator

The impact is measured through the "IPCC 2013 GWP 100a" method.

Electricity impact calculation method

Following guidelines from the GHG Protocol, the impact of electricity is calculated using the location-based approach. This means that the emission factors used represent the average annual carbon intensity of the power grid in the country the processes take place in.

Hypothesis





Environmental Impact Assessment

System Boundaries

The scope of this research includes the complete lifecycle of a notebook from raw material extraction to disposal options for each material, which is the cradle-to-grave perspective.

Exclusions


The impact of secondary packaging and writing utensils are excluded from this assessment.








greenly



Climate Change



Step	Impact (g CO₂ eq)	Percentage (%)
Raw Material Extraction and Processing	439.4	58.28 %
End-of-Life Treatment	148.97	19.76 %
Manufacturing	113.65	15.07 %
Transportation and Distribution	51.92	6.89 %


TOTAL	753.94	100.00 %
	, 55.5 .	100.0070





Climate Change - Raw Material Extraction and






Activity	Emission Factor Num	Quantity	Impact (g CO₂ eq)	Percentage (%)
Sourcing of raw material (coloured kraft paper)	2	0.38	424.12	96.52 %
Sourcing of raw material (adhesive)	1	2.8 · 10^-3	15.28	3.48 %


TOTAL 439.4 100.00 %







Climate Change - Manufacturing



Activity	Emission Factor Num	Quantity	Impact (g CO ₂ eq)	Percentage (%)
Electricity usage during material transformation (coloured kraft paper)	4	0.13	96.86	85.23 %
Natural gas usage during material transformation (coloured kraft paper)	3	0.07	13.02	11.46 %
Electricity usage during material transformation (adhesive)	4	5.2 · 10^-3	3.76	3.31 %


TOTAL		113.65	100.00 %





Climate Change - Transportation and

Distribution




Activity	Emission Factor Num	Quantity	lmpact (g CO₂ eq)	Percentage (%)
Freight	5	0.26	51.92	100.00 %

51.92 **TOTAL** 100.00 %





Climate Change - End-of-Life Treatment



Activity	Emission Factor Num	Quantity	Impact (g CO ₂ eq)	Percentage (%)
End of life (coloured kraft paper)	7	0.25	145.52	97.68 %
End of life (adhesive)	6	2.54 · 10^-3	3.45	2.32 %

TOTAL	148.97	100.00 %





Contact us

Alexis Normand CEO www.greenly.earth

greenly