

MY T ONE S1 LOW



BASIC INFORMATION

Article no.	715-64133
Safety category	S1
Standard	CE EN ISO 20345:2022
DGUV	No
Model	Low cut

SIZE RANGE

Width	FR	UK
W	35-48	2-13

DESCRIPTION

Low cut safety shoe S1 leather upper, PU/PU outsole

RECOMMENDED FOR

Construction
Indoor
Outdoor

MATERIAL PROPERTIES

Safety toecap	Steel
Perforation-resistant insert	None
Upper	Printed leather
Midsole	PU
Outsole	PU
Inlay sole	EVA
Lining	Polyester
Closure	Laces, Polyester, 110 cm
Shank	None

SAFETY FEATURES

A	- Antistatic
F0	- Fuel and oil resistant outsole
SC	- PU injected abrasion resistant scuff cap
SR	- Slip resistance

FEATURES AND TECHNOLOGIES

Dual density sole

PACKAGING

35-48

Gross weight (pair) (kg)	1.223
Net weight (pair) (kg)	0.998
Unit package LxHxW (mm)	350x295x124
Units per carton	10
Carton LxHxW (mm)	650x310x370
Units per container 20 foot	2300-2500
Units per container 40 foot	5200-5400
Units per container 40 foot HQ	6000-6300