



EU-TYPE EXAMINATION CERTIFICATE



The following model of Personal Protective Equipment has been subjected to an EU-type examination in accordance with the module B of the PPE regulation (2016/425) and has been shown to satisfy to essential health and safety requirements.

Certificate N° 0075/1142/162/02/25/0441

Issued by CTC, Notified Body N°0075, to the following model of personal protective equipment :

Manufacturer : **INTERSAFE NETHERLANDS B.V.**
carrosserieweg 5, 3445 BC, WOERDEN
THE NETHERLANDS

Description

PPE Type : *protective glove against mechanical risks*

Product reference : **MH-1805-PNC**

Article code : 209578 / 19827139(06) 209578 / 19827128(07) 209578 / 19827117(08) 209578 / 19827106(09) 209578 / 19827094(10) 209578 / 19827083(11) 209578 / 19827072(12)

Glove description : HPPE (high performance polyethylene) PU Palm Coated Gloves, Knit Wrist

Available sizes : 6-209578 / 19827139(06) 7-209578 / 19827128(07) 8-209578 / 19827117(08) 9-209578 / 19827106(09) 10-209578 / 19827094(10) 11-209578 / 19827083(11) 12-209578 / 19827072(12)

Pictures :



My-T-Gear®

209578 / 19827094 (10)
MH-1805-PNC -10-
EN388:2016+A1:2018



Reference standard :

Levels of performance / class of protection

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.
« 0 » indicates that the glove falls below the minimum performance level for the individual hazard.

EN ISO 21420:2020

-

EN 388:2016 + A1:2018

3 X 4 2 C

At the date of the certificate, the product is in compliance with Annex XVII of REACH regulation (n° 1907/2006 and revisions)

Full description of the PPE, reference rules verified in the context of the EU-type examination and information given on the product are detailed in the manufacturer's technical file and the user instructions index 01 dated from February 2025.

NOTA : Any modification to new items of the personal protective equipment object of this EU type approval certificate or any modification of the information contained in the manufacturer technical file which served for the deliverance of the EU type approval certificate (change of address, change of company status) should be brought to the attention of the notified body in accordance with Annex V §7.2 of Regulation 2016/425. Any marking on the PPE which is not concerned by the Regulation (UE) 2016/425, is not covered by this certificate.

Issued in Lyon by
Didier GUISSADO
Certification deputy director



Date of first issue: 26 February 2025
Date of end of validity: 26 February 2030

In application of the Regulation 2016/425 of the European parliament and the Council of 9th March 2016 related to Personal Protective Equipment and repealing the Directive 89/686/EEC.



Accreditation n° 5-0594
Scope available on:
www.cofrac.fr

www.ctcgroupe.com

cemarking@ctcgroupe.com

CTC - 4, rue Hermann Frenkel - 69367 Lyon cedex 07 - France
Tél. : +33 (0)4 72 76 10 10 - Fax : +33 (0)4 72 76 10 00 - ctclyon@ctcgroupe.com

Comité Professionnel de Développement Économique (CPDE) Cuir Chaussure Maroquinerie Ganterie
Loi 78-654 du 22.06.1978 - Siret 77564972600160 - Code NAF 9412Z - TVA FR 88775649726



INTERSAFE NETHERLANDS B.V.

MANUFACTURER'S TECHNICAL FILE TO THE PPE REGULATION 2016/425

Reference of the product :

MH-1805-PNC

Article code :

**209578 / 19827139(06)
209578 / 19827128(07)
209578 / 19827117(08)
209578 / 19827106(09)
209578 / 19827094(10)
209578 / 19827083(11)
209578 / 19827072(12)**

Technical file index :

01

Last update :

February 2025

IDENTIFICATION

Reference of the product :	:	MH-1805-PNC
		209578 / 19827139(06)
		209578 / 19827128(07)
		209578 / 19827117(08)
Article code :	:	209578 / 19827106(09)
		209578 / 19827094(10)
		209578 / 19827083(11)
		209578 / 19827072(12)
Basic Model		
Technical file index :	:	01
Last update :	:	February 2025

Manufacturer :

INTERSAFE NETHERLANDS B.V.

carrosserieweg 5, 3445 BC, WOERDEN

THE NETHERLANDS

tel : +31622929340

fax : /

Factory :

Belin Industry (HK) Co., Limited

Room 902, Building.6, No. 333 Haibo Road, Jiading, Shanghai, 201803

CHINA

tel: +86 13818332762

fax: /

GLOVE DESCRIPTION

General glove description and intended use:

HPPE (high performance polyethylene) PU Palm Coated Gloves, Knit Wrist

This glove is designed against mechanical risks.

Type of coating finish : smooth

Visual description (picture back and palm sides) :



Risk assessment (Essential Health and Safety Requirement. Annex II - PPE Regulation)

		Applicable	Covered by
§1	Requirements defined in the Annex II §1 are applicable to all PPE	☒	☒ Standard ☒ Instruction for use ☒ Marking
§1.4	Manufacturer's instructions and information is available	☒	☒ Standard ☒ Instruction for use ☐ Marking
§2.5	PPE which may be caught up during use	☒	☐ Standard ☒ Instruction for use ☐ Marking
§2.12	PPE bearing one or more identification markings or indicators directly or indirectly relating to health and safety	☒	☒ Standard ☒ Instruction for use ☒ Marking
§3.3	The PPE is intended to protect against mechanical injuries	☒	☒ Standard ☒ Instruction for use ☒ Marking

Glove constitution :

	Reference	Color	Material	Surfacic mass (g/m ²)	G	Thickness
Palm		Grey	PU			0.1mm
		Black/ White	high performance polyethylene	353g/m ²	18G	
	thumb crotch	Black	Nitrile			0.2mm
Back		Black/ White	high performance polyethylene	353g/m ²	18G	
Cuff		Black/ White	high performance polyethylene/ elastic	567g/m ²	18G	
Binding		White, Grey, Yellow, Brown, Black, Blue	Polyester			

PROTECTION SCOPE

This glove meets the essential requirements of the Personal Protective Equipment Regulation 2016/425.

This glove is designed against mechanical risks.

It is a category II product.

GENERAL REQUIREMENTS

Standard EN ISO 21420 : 2020

Dexterity : 5

Available size range: 6-209578 / 19827139(06) 7-209578 / 19827128(07) 8-209578 / 19827117(08) 9-209578 / 19827106(09) 10-209578 / 19827094(10) 11-209578 / 19827083(11) 12-209578 / 19827072(12)

The hand sizing system is based on hand circumference and hand length as defined in EN ISO 21420 Annex B table B.1

SPECIFIC REQUIREMENTS AND PERFORMANCE LEVELS

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

« 0 » indicates that the glove falls below the minimum performance level for the individual hazard.

Mechanical hazard EN 388:2016 + A1:2018

Protection offered	Performance levels
Abrasion resistance	3
Blade cut resistance	X
Tear strength resistance	4
Puncture resistance	2
Cut Resistance method (EN ISO 13997)	C
Impact Protection	N/A

The levels of performance have been measured on the palm.

TEST REPORTS

Laboratory	CTC	Other
EN ISO 21420 + innocuousness	S241213160_1 S241213175_1 S250201054_1 S241213159_1 (black nitrile)	
EN 388	S241213160_1 S250100644_1	

MARKING - PACKAGING

Information printed on the glove :

Logo of Manufacturer :

Logo 

Glove's reference : MH-1805-PNC

Article Code : 209578 / 19827139(06) 209578 / 19827128(07) 209578 / 19827117(08) 209578 / 19827106(09)
209578 / 19827094(10) 209578 / 19827083(11) 209578 / 19827072(12)

Size indicator

Pictograms related to risks against which protection is offered with performance levels

Information pictogram

Address of Manufacturer :

Date of Manufacture (month/year) and/or serial/batch number :

Date of obsolescence (month/year) if applicable:

Marking example :

My-T-Gear®
209578 / 19827094 (10)
MH-1805-PNC -10-
EN388:2016+A1:2018
  
3 X 4 2 C

My-T-Gear®

Intersafe Netherlands B.V.
 Carrosserieweg 5
 3445 BC WOERDEN
 THE NETHERLANDS
www.intersafe.eu

PO.no: 123456
 Mfg.date : 01-2025
 MADE IN CHINA

Method of marking on the glove :

screenprinted on the back of gloves and label

Packaging suitable for transport:

12pairs/polygag; 12dozen/carton

PPE subject to ageing :

The design performance can not be significantly affect by ageing when stored in appropriate conditions (humidity, temperature, clean , ventilated, light).

Cleaning instructions:

The gloves are not washable.

MEANS OF CONTROL

First we put the high-pressure polyethylene liner gloves on the mould.

The second we dip the gloves into the PU, then the gloves will be put in the oven to get dry and about 2 hours later, we take out gloves from the mould and put the gloves in the oven again. After 1 hours later, the PU on the surface of gloves become completely dry.

Then, we print the logo on the back of gloves.

Final, we pack the gloves.

We check the quality ever 3 hours every day, and evey shipment, total 3 times to check the quality from each orders High-pressure polyethylene liner is customized, storage exceeds the shelf life will be treated as the inventory. The finished products will be checked from the shape, size ,color, hand feeling, wear comfort, and also the tensile between the fingers and rip dropped calls and other routine examination.

Defective products generally do the domestic discount deal, Separately storage for the products will avoid secondary pollution and non-green product mixed, or any other reasons. frequency of EN388 EN ISO21420 tests once a year.

INSTRUCTIONS FOR USE

INTERSAFE NETHERLANDS B.V.

carrosserieweg 5, 3445 BC, WOERDEN

THE NETHERLANDS

Glove reference : MH-1805-PNC

Article code: 209578 / 19827139(06) 209578 / 19827128(07) 209578 /
19827117(08) 209578 / 19827106(09) 209578 / 19827094(10)
209578 / 19827083(11) 209578 / 19827072(12)

User notice index : 01

Last update : February 2025

Glove description :

HPPE (high performance polyethylene) PU Palm Coated Gloves, Knit Wrist

This glove is a personal protective equipment belonging to the category II.

It meets the requirements of the PPE Regulation 2016/425 : innocuousness, comfort, solidity.

It has been subject to a UE-type Examination performed by :

C.T.C. (0075)
4, rue Hermann Frenkel
69367 LYON Cedex 07
FRANCE

The glove meets the requirements of the standard EN ISO 21420:2020 « Protective Gloves - General requirements and test methods ».

Dexterity: 5

Available size range: 6-209578 / 19827139(06) 7-209578 / 19827128(07) 8-209578 / 19827117(08) 9-209578 / 19827106(09) 10-209578 /
19827094(10) 11-209578 / 19827083(11) 12-209578 / 19827072(12)

The hand sizing system is based on hand circumference and hand length as defined in EN ISO 21420 Annex B.

Information about marking

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

« 0 » indicates that the glove falls below the minimum performance level for the individual hazard.



The CE marking means that this product meets the requirements of the regulation 2016/425

Mechanical hazard - EN 388:2016 + A1:2018



3 X 4 2 C

Levels of performance

Abrasion resistance	3	(on 4 maxi)
Blade cut resistance	X	(on 5 maxi)
Tear resistance	4	(on 4 maxi)
Puncture resistance	2	(on 4 maxi)
Cut Resistance method (EN ISO 13997)	C	(A to F)
Impact Protection		



Read carefully the instructions for use provided with the product

Protection limit :

Users should be warned that gloves should not be worn when there is a risk of entanglement by moving parts of machines.

This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.

The protection against risks or hazards which are not mentioned in this document is not warranted.

These levels of performance are obtained from the tests done according to conditions defined by the applicable standards.

The levels of performance mentioned are only valid for new gloves, not washed, nor regenerated.

Before use, the glove shall be visually inspected for any defect or imperfections. In case of deterioration, the gloves must be scrapped (abrasion, cut, tear...).

For gloves with two or more layers the overall classification does not necessarily reflect the performance of the outermost layer.

The levels of performance against mechanical risks are only valid for the palm of the glove.

Storage and cleaning notice

Keep in its original packaging, under ordinary temperature and humidity conditions and in clean, covered and ventilated premises.

The gloves are not washable.

PPE subject to ageing :

The design performance can not be significantly affect by ageing when stored in appropriate conditions (humidity, temperature, clean , ventilated, light).

Declaration of conformity :

Available on : www.intersafe.eu/docs

My-T-Gear®

209578 / 19827094 (10)

MH-1805-PNC -10-

EN388:2016+A1:2018



3 X 4 2 C

My-T-Gear®

Intersafe Netherlands B.V.
Carrosserieweg 5
3445 BC WOERDEN
THE NETHERLANDS
www.intersafe.eu

PO.no: 123456
Mfg.date : 01-2025
MADE IN CHINA