

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixtures
 Product name : Ethyl Alcohol, 70% v/v
 Product code : VT270
 Other means of identification : Ethanol, Denatured, 70% v/v

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : For laboratory and manufacturing use only.

1.3. Details of the supplier of the safety data sheet

Val Tech Diagnostics, A Division of LabChem Inc
 Jackson's Pointe Commerce Park Building 1000
 1010 Jackson's Pointe Court
 Zelienople, PA 16063
 T 412-826-5230
 F 724-473-0647

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 or 011-703-527-3887

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Liq. 3 H226
 Skin Irrit. 2 H315
 Eye Irrit. 2A H319
 Repr. 2 H361
 STOT SE 3 H336
 STOT SE 1 H370

Full text of H statements : see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H226 - Flammable liquid and vapour
 H315 - Causes skin irritation
 H319 - Causes serious eye irritation
 H336 - May cause drowsiness or dizziness
 H361 - Suspected of damaging fertility or the unborn child
 H370 - Causes damage to organs (central nervous system, optic nerve) (oral, Dermal)

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use.
 P202 - Do not handle until all safety precautions have been read and understood.
 P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking.
 P233 - Keep container tightly closed.
 P240 - Ground/bond container and receiving equipment.
 P241 - Use explosion-proof electrical, lighting, ventilating equipment
 P242 - Use only non-sparking tools.
 P243 - Take precautionary measures against static discharge.
 P260 - Do not breathe the mist, spray, vapors.
 P264 - Wash exposed skin thoroughly after handling.
 P270 - Do not eat, drink or smoke when using this product.
 P271 - Use only outdoors or in a well-ventilated area.
 P280 - Wear eye protection, face protection, protective clothing, protective gloves.

Ethyl Alcohol, 70% v/v

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P308+P313 - IF exposed or concerned: Get medical advice/attention.
P312 - Call a POISON CENTER or doctor/physician if you feel unwell.
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P363 - Wash contaminated clothing before reuse.
P370+P378 - In case of fire: Use carbon dioxide (CO₂), powder, alcohol-resistant foam to extinguish
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P405 - Store locked up.
P501 - Dispose of contents/container to comply with local, state and federal regulations
P235 - Keep cool.

2.3. Other hazards

Other hazards not contributing to the classification : None.

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

Full text of H-phrases: see section 16

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Ethanol	(CAS-No.) 64-17-5	52.3 - 57.5	Flam. Liq. 2, H225 Carc. 1A, H350 Repr. 2, H361
Water	(CAS-No.) 7732-18-5	35.9 - 42.3	Not classified
Isopropyl Alcohol (2-Propanol)	(CAS-No.) 67-63-0	2.8 - 3.3	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H335
Methanol	(CAS-No.) 67-56-1	2.6 - 3.3	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 STOT SE 1, H370

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with labored breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital. Never give alcohol to drink.

First-aid measures after inhalation : Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

First-aid measures after skin contact : Rinse with water. Take victim to a doctor if irritation persists.

First-aid measures after eye contact : Rinse immediately with plenty of water. Do not apply neutralizing agents. Take victim to an ophthalmologist if irritation persists.

First-aid measures after ingestion : Rinse mouth with water. Do not induce vomiting. Call Poison Information Centre (www.big.be/antigif.htm). Consult a doctor/medical service if you feel unwell. Ingestion of large quantities: immediately to hospital.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : EXPOSURE TO HIGH CONCENTRATIONS: Dry/sore throat. Coughing. Irritation of the respiratory tract. Irritation of the nasal mucous membranes. Respiratory difficulties. Central nervous system depression. Symptoms similar to those listed under ingestion.

Symptoms/effects after skin contact : Slight irritation.

Ethyl Alcohol, 70% v/v

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after eye contact	: Redness of the eye tissue. Lacrimation. ON CONTINUOUS EXPOSURE/CONTACT: Irritation of the eye tissue.
Symptoms/effects after ingestion	: AFTER ABSORPTION OF LARGE QUANTITIES: Risk of aspiration pneumonia. Red skin. Body temperature rise. Damp/clammy skin. Excited/restless. Accelerated heart action. Central nervous system depression. Dizziness. Narcosis. Headache. Drunkenness. Nausea. Vomiting. Disturbed motor response. Coordination disorders. Visual disturbances. Impaired concentration. Delusions. Disturbed sensation of pain. Disturbances of heart rate. Disturbances of consciousness. Tremor. Cramps/uncontrolled muscular contractions. Dilated pupils.
Chronic symptoms	: ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Dry skin. Gastrointestinal complaints. Enlargement/affection of the liver. Change in the haemogramme/blood composition. Cardiac and blood circulation effects. High arterial pressure. Impairment of the nervous system. Behavioural disturbances. Mental confusion. Disturbed tactile sensibility. Tremor. Affection of the bone marrow. Affection of the endocrine system. Weakening of the immune system.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Alcohol-resistant foam. BC powder. Carbon dioxide.
Unsuitable extinguishing media	: Solid water jet ineffective as extinguishing medium.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: DIRECT FIRE HAZARD. Highly flammable. Gas/vapor flammable with air within explosion limits. INDIRECT FIRE HAZARD. May be ignited by sparks. Gas/vapor spreads at floor level: ignition hazard. Reactions involving a fire hazard: see "Reactivity Hazard".
Explosion hazard	: DIRECT EXPLOSION HAZARD. Gas/vapour explosive with air within explosion limits. INDIRECT EXPLOSION HAZARD. may be ignited by sparks. Reactions with explosion hazards: see "Reactivity Hazard".
Reactivity	: Upon combustion: CO and CO ₂ are formed. Reacts violently with many compounds e.g.: with (strong) oxidizers: (increased) risk of fire/explosion. Violent to explosive reaction with (some) acids.

5.3. Advice for firefighters

Firefighting instructions	: Cool tanks/drums with water spray/remove them into safety. Do not move the load if exposed to heat.
Protection during firefighting	: Heat/fire exposure: compressed air/oxygen apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No smoking.
------------------	--

6.1.1. For non-emergency personnel

Protective equipment	: Gloves. Protective goggles. Protective clothing. Large spills/in enclosed spaces: compressed air apparatus. See "Material-Handling" to select protective clothing.
Emergency procedures	: Keep upwind. Mark the danger area. Consider evacuation. Seal off low-lying areas. Close doors and windows of adjacent premises. Stop engines and no smoking. No naked flames or sparks. Spark- and explosion-proof appliances and lighting equipment. Keep containers closed. Wash contaminated clothes.

6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection. Avoid breathing mist, spray.
Emergency procedures	: Ventilate area.

6.2. Environmental precautions

Prevent spreading in sewers.

6.3. Methods and material for containment and cleaning up

For containment	: Contain released substance, pump into suitable containers. Consult "Material-handling" to select material of containers. Plug the leak, cut off the supply. Dam up the liquid spill. Try to reduce evaporation. Measure the concentration of the explosive gas-air mixture. Dilute/disperse combustible gas/vapour with water curtain. Provide equipment/receptacles with earthing. Do not use compressed air for pumping over spills.
-----------------	--

Ethyl Alcohol, 70% v/v

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methods for cleaning up : Take up liquid spill into a non combustible material e.g.: sand, earth, vermiculite or kieselguhr, powdered limestone. Scoop absorbed substance into closing containers. See "Material-handling" for suitable container materials. Carefully collect the spill/leftovers. Damaged/cooled tanks must be emptied. Do not use compressed air for pumping over spills. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Comply with the legal requirements. Remove contaminated clothing immediately. Clean contaminated clothing. Handle uncleaned empty containers as full ones. Thoroughly clean/dry the installation before use. Do not discharge the waste into the drain. Do not use compressed air for pumping over. Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Observe normal hygiene standards. Keep container tightly closed. Measure the concentration in the air regularly. Work under local exhaust/ventilation.

Hygiene measures : Wash exposed skin thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/... equipment.

Storage conditions : Keep container tightly closed. Keep only in the original container in a cool, well ventilated place away from : incompatible materials. Keep in fireproof place.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

Heat-ignition : KEEP SUBSTANCE AWAY FROM: heat sources. ignition sources.

Prohibitions on mixed storage : KEEP SUBSTANCE AWAY FROM: oxidizing agents. strong acids. water/moisture.

Storage area : Keep out of direct sunlight. Store in a dry area. Ventilation at floor level. Fireproof storeroom. Provide for an automatic sprinkler system. Provide for a tub to collect spills. Provide the tank with earthing. Meet the legal requirements.

Special rules on packaging : SPECIAL REQUIREMENTS: closing. dry. clean. correctly labelled. meet the legal requirements. Secure fragile packagings in solid containers.

Packaging materials : SUITABLE MATERIAL: stainless steel. aluminium. iron. copper. nickel. synthetic material. glass. MATERIAL TO AVOID: No data available.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Ethyl Alcohol, 70% v/v		
USA ACGIH	ACGIH STEL (ppm)	1000 ppm (Ethanol; USA; Short time value; TLV - Adopted Value)
USA OSHA	OSHA PEL (TWA) (mg/m ³)	1900 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
Ethanol (64-17-5)		
USA ACGIH	ACGIH STEL (ppm)	1000 ppm (Ethanol; USA; Short time value; TLV - Adopted Value)
USA OSHA	OSHA PEL (TWA) (mg/m ³)	1900 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
Isopropyl Alcohol (2-Propanol) (67-63-0)		
USA ACGIH	ACGIH TWA (ppm)	200 ppm (2-propanol; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
USA ACGIH	ACGIH STEL (ppm)	400 ppm (2-propanol; USA; Short time value; TLV - Adopted Value)
USA OSHA	OSHA PEL (TWA) (mg/m ³)	980 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	400 ppm

Ethyl Alcohol, 70% v/v

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methanol (67-56-1)		
USA ACGIH	ACGIH TWA (ppm)	200 ppm (Methanol; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
USA ACGIH	ACGIH STEL (ppm)	250 ppm (Methanol; USA; Short time value; TLV - Adopted Value)
USA OSHA	OSHA PEL (TWA) (mg/m ³)	260 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm

8.2. Exposure controls

- Appropriate engineering controls : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Provide local exhaust or general room ventilation.
- Personal protective equipment : Safety glasses. Gloves. Protective clothing. High gas/vapor concentration: gas mask with filter type A.



- Materials for protective clothing : GIVE EXCELLENT RESISTANCE: butyl rubber. viton. GIVE GOOD RESISTANCE: neoprene. tetrafluoroethylene. GIVE LESS RESISTANCE: nitrile rubber. polyethylene. GIVE POOR RESISTANCE: natural rubber. PVA. PVC.
- Hand protection : Gloves.
- Eye protection : Safety glasses.
- Skin and body protection : Protective clothing.
- Respiratory protection : Wear gas mask with filter type A if conc. in air > exposure limit.
- Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Appearance : Liquid.
- Molecular mass : 46.07 g/mol
- Color : Colourless.
- Odor : Alcohol odour. Pleasant odour.
- Odor threshold : 100 ppm
188 mg/m³
- pH : No data available
- Relative evaporation rate (butyl acetate=1) : 2.4
- Relative evaporation rate (ether=1) : 8.3
- Melting point : -115 °C
- Freezing point : No data available
- Boiling point : 78 °C
- Flash point : 25 °C
- Critical temperature : 243 °C
- Auto-ignition temperature : 363 °C
- Decomposition temperature : No data available
- Flammability (solid, gas) : No data available
- Vapor pressure : 59 hPa (20 °C)
- Vapor pressure at 50 °C : 300 hPa (50 °C)
- Critical pressure : 63840 hPa
- Relative vapor density at 20 °C : 1.6
- Relative density : 0.79
- Relative density of saturated gas/air mixture : 1.04
- Specific gravity / density : 0.881 g/l

Ethyl Alcohol, 70% v/v

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Solubility	: Soluble in water. Soluble in ether. Soluble in acetone. Soluble in chloroform. Soluble in oils/fats. Soluble in methanol. Soluble in acids. Water: Complete Ethanol: Not applicable Ether: Complete Acetone: Complete
Log Pow	: -0.31 (Experimental value)
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 0.0012 Pa.s (20 °C)
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: 3.3 - 19.0 vol % 67 - 290 g/m ³

9.2. Other information

Specific conductivity	: 130000 pS/m
Saturation concentration	: 112 g/m ³
VOC content	: 100 %
Other properties	: Gas/vapour heavier than air at 20°C. Clear. Hygroscopic. Volatile. Substance has neutral reaction.

SECTION 10: Stability and reactivity

10.1. Reactivity

Upon combustion: CO and CO₂ are formed. Reacts violently with many compounds e.g.: with (strong) oxidizers: (increased) risk of fire/explosion. Violent to explosive reaction with (some) acids.

10.2. Chemical stability

Hygroscopic.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Ethyl Alcohol, 70% v/v	
LD50 oral rat	10740 mg/kg body weight (Rat; OECD 401: Acute Oral Toxicity; Experimental value)
LD50 dermal rabbit	> 16000 mg/kg (Rabbit; Literature study)
Ethanol (64-17-5)	
LD50 oral rat	10740 mg/kg (Rat; Experimental value,Rat; Experimental value)
LD50 dermal rabbit	> 16000 mg/kg (Rabbit; Literature study)
Isopropyl Alcohol (2-Propanol) (67-63-0)	
LD50 dermal rabbit	12870 mg/kg (Rabbit; Experimental value; Equivalent or similar to OECD 402; 16.4; Rabbit)
LC50 inhalation rat (mg/l)	73 mg/l/4h (Rat)
Methanol (67-56-1)	
LD50 oral rat	> 5000 mg/kg (Rat; BASF test; Literature study; 1187-2769 mg/kg bodyweight; Rat; Weight of evidence)
LD50 dermal rabbit	15800 mg/kg (Rabbit; Literature study)
LC50 inhalation rat (mg/l)	85 mg/l/4h (Rat; Literature study)

Ethyl Alcohol, 70% v/v

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methanol (67-56-1)	
LC50 inhalation rat (ppm)	64000 ppm/4h (Rat; Literature study)

Water (7732-18-5)	
LD50 oral rat	≥ 90000 mg/kg

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
	Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified

Ethanol (64-17-5)	
IARC group	1 - Carcinogenic to humans

Isopropyl Alcohol (2-Propanol) (67-63-0)	
IARC group	3 - Not classifiable

Reproductive toxicity	: Suspected of damaging fertility or the unborn child. Based on available data, the classification criteria are not met
Specific target organ toxicity – single exposure	: May cause drowsiness or dizziness. Causes damage to organs (central nervous system, optic nerve) (oral, Dermal).
Specific target organ toxicity – repeated exposure	: Not classified Based on available data, the classification criteria are not met
Aspiration hazard	: Not classified Based on available data, the classification criteria are not met
Potential Adverse human health effects and symptoms	: Harmful if swallowed. Based on available data, the classification criteria are not met.
Symptoms/effects after inhalation	: EXPOSURE TO HIGH CONCENTRATIONS: Dry/sore throat. Coughing. Irritation of the respiratory tract. Irritation of the nasal mucous membranes. Respiratory difficulties. Central nervous system depression. Symptoms similar to those listed under ingestion.
Symptoms/effects after skin contact	: Slight irritation.
Symptoms/effects after eye contact	: Redness of the eye tissue. Lacrimation. ON CONTINUOUS EXPOSURE/CONTACT: Irritation of the eye tissue.
Symptoms/effects after ingestion	: AFTER ABSORPTION OF LARGE QUANTITIES: Risk of aspiration pneumonia. Red skin. Body temperature rise. Damp/clammy skin. Excited/restless. Accelerated heart action. Central nervous system depression. Dizziness. Narcosis. Headache. Drunkenness. Nausea. Vomiting. Disturbed motor response. Coordination disorders. Visual disturbances. Impaired concentration. Delusions. Disturbed sensation of pain. Disturbances of heart rate. Disturbances of consciousness. Tremor. Cramps/uncontrolled muscular contractions. Dilated pupils.
Chronic symptoms	: ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Dry skin. Gastrointestinal complaints. Enlargement/affection of the liver. Change in the haemogramme/blood composition. Cardiac and blood circulation effects. High arterial pressure. Impairment of the nervous system. Behavioural disturbances. Mental confusion. Disturbed tactile sensibility. Tremor. Affection of the bone marrow. Affection of the endocrine system. Weakening of the immune system.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008.
Ecology - air	: Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009). Not included in the list of substances which may contribute to the greenhouse effect (Regulation (EC) No 842/2006). TA-Luft Klasse 5.2.5.
Ecology - water	: Not harmful to fishes (LC50(96h) >1000 mg/l). Not harmful to invertebrates (Daphnia). Slightly harmful to algae (EC50 (72h): 100 - 1000 mg/l). Harmful to plankton. Not harmful to bacteria (EC50 >1000 mg/l). No inhibition of activated sludge.

Ethyl Alcohol, 70% v/v	
LC50 fish 1	14200 mg/l (LC50; US EPA; 96 h; Pimephales promelas; Flow-through system; Fresh water; Experimental value)

Ethyl Alcohol, 70% v/v

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ethanol (64-17-5)	
LC50 fish 1	14200 mg/l (LC50; US EPA; 96 h; Pimephales promelas; Flow-through system; Fresh water; Experimental value)
Isopropyl Alcohol (2-Propanol) (67-63-0)	
LC50 fish 2	9640 mg/l (LC50; OECD 203; Fish, Acute Toxicity Test; 96 h; Pimephales promelas; Flow-through system; Fresh water; Experimental value)
EC50 Daphnia 2	13299 mg/l (EC50; Other; 48 h; Daphnia magna)
Threshold limit algae 1	> 1000 mg/l (EC50; UBA; 72 h; Scenedesmus subspicatus)
Methanol (67-56-1)	
LC50 fish 1	15400 mg/l (LC50; EPA 660/3 - 75/009; 96 h; Lepomis macrochirus; Flow-through system; Fresh water; Experimental value)
EC50 Daphnia 1	> 10000 mg/l (EC50; DIN 38412-11; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
LC50 fish 2	10800 mg/l (LC50; 96 h; Salmo gairdneri)

12.2. Persistence and degradability

Ethyl Alcohol, 70% v/v	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil.
Biochemical oxygen demand (BOD)	0.8 - 0.967 g O □/g substance
Chemical oxygen demand (COD)	1.7 g O □/g substance
ThOD	2.1 g O □/g substance
BOD (% of ThOD)	0.43
Ethanol (64-17-5)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil.
Biochemical oxygen demand (BOD)	0.8 - 0.967 g O □/g substance
Chemical oxygen demand (COD)	1.7 g O □/g substance
ThOD	2.1 g O \bar{a} ngsubst
BOD (% of ThOD)	0.43
Isopropyl Alcohol (2-Propanol) (67-63-0)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. No test data on mobility of the substance available.
Biochemical oxygen demand (BOD)	1.19 g O □/g substance
Chemical oxygen demand (COD)	2.23 g O □/g substance
ThOD	2.4 g O □/g substance
Methanol (67-56-1)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil.
Biochemical oxygen demand (BOD)	0.6 - 1.12 g O □/g substance
Chemical oxygen demand (COD)	1.42 g O □/g substance
ThOD	1.5 g O □/g substance
BOD (% of ThOD)	0.8 (Literature study)
Water (7732-18-5)	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

Ethyl Alcohol, 70% v/v	
BCF fish 1	1 (BCF; Other; 72 h; Cyprinus carpio; Static system; Fresh water; Read-across)
Log Pow	-0.31 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Ethanol (64-17-5)	
BCF fish 1	1 (BCF; Other; 72 h; Cyprinus carpio; Static system; Fresh water; Read-across)
Log Pow	-0.31 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Isopropyl Alcohol (2-Propanol) (67-63-0)	
Log Pow	0.05 (Weight of evidence approach; Other; 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

Ethyl Alcohol, 70% v/v

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methanol (67-56-1)	
BCF fish 1	< 10 (BCF; 72 h; Leuciscus idus)
Log Pow	-0.77 (Experimental value; Other)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

Water (7732-18-5)	
Bioaccumulative potential	Not established.

12.4. Mobility in soil

Ethyl Alcohol, 70% v/v	
Surface tension	0.022 N/m (20 °C)
Log Koc	Koc,PCKOCWIN v1.66; 1; Read-across

Ethanol (64-17-5)	
Surface tension	0.022 N/m (20 °C)
Log Koc	Koc,PCKOCWIN v1.66; 1; Read-across

Isopropyl Alcohol (2-Propanol) (67-63-0)	
Surface tension	0.021 N/m (25 °C)

Methanol (67-56-1)	
Surface tension	0.023 N/m (20 °C)
Log Koc	Koc,PCKOCWIN v1.66; 1; Calculated value

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Recycle by distillation. Remove to an authorized waste incinerator for solvents with energy recovery. Do not discharge into surface water. May be discharged to wastewater treatment installation.

Additional information : LWCA (the Netherlands): KGA category 03. Hazardous waste according to Directive 2008/98/EC.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with DOT

Transport document description : UN1987 Alcohols, n.o.s. (ethanol, methanol), 3, III

UN-No.(DOT) : 1987

DOT NA no. : UN1987

Proper Shipping Name (DOT) : Alcohols, n.o.s.
ethanol, methanol

Transport hazard class(es) (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : III - Minor Danger

Ethyl Alcohol, 70% v/v

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)	: 172 - This entry includes alcohol mixtures containing up to 5% petroleum products. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 4b;150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 220 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

Additional information

Other information : No supplementary information available.

ADR

Transport document description	: UN 1170 ethanol (ethyl alcohol), 3, II, (D/E)
Packing group (ADR)	: II
Class (ADR)	: 3 - Flammable liquid
Hazard identification number (Kemler No.)	: 33
Classification code (ADR)	: F1
Hazard labels (ADR)	: 3 - Flammable liquids



Orange plates



Tunnel restriction code : D/E

Transport by sea

UN-No. (IMDG)	: 1987
Proper Shipping Name (IMDG)	: ALCOHOLS, N.O.S.
Class (IMDG)	: 3 - Flammable liquids
Packing group (IMDG)	: III - substances presenting low danger
EmS-No. (1)	: F-E
EmS-No. (2)	: S-D

Air transport

UN-No. (IATA)	: 1987
Proper Shipping Name (IATA)	: Alcohols, n.o.s.
Class (IATA)	: 3 - Flammable Liquids
Packing group (IATA)	: III - Minor Danger

Ethyl Alcohol, 70% v/v

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

Ethyl Alcohol, 70% v/v

SARA Section 311/312 Hazard Classes	Physical hazard - Flammable (gases, aerosols, liquids, or solids) Health hazard - Serious eye damage or eye irritation Health hazard - Skin corrosion or Irritation Health hazard - Specific target organ toxicity (single or repeated exposure) Health hazard - Reproductive toxicity
-------------------------------------	--

Ethanol (64-17-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Isopropyl Alcohol (2-Propanol) (67-63-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313

SARA Section 311/312 Hazard Classes	Physical hazard - Flammable (gases, aerosols, liquids, or solids) Health hazard - Serious eye damage or eye irritation Health hazard - Specific target organ toxicity (single or repeated exposure)
-------------------------------------	---

Methanol (67-56-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313

RQ (Reportable quantity, section 304 of EPA's List of Lists)	5000 lb
SARA Section 311/312 Hazard Classes	Physical hazard - Flammable (gases, aerosols, liquids, or solids) Health hazard - Acute toxicity (any route of exposure) Health hazard - Specific target organ toxicity (single or repeated exposure)

Water (7732-18-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

Ethyl Alcohol, 70% v/v

WHMIS Classification	Class B Division 3 - Combustible Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
----------------------	---

Isopropyl Alcohol (2-Propanol) (67-63-0)

WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	--

Methanol (67-56-1)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	--

Water (7732-18-5)

WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
----------------------	---

EU-Regulations

Isopropyl Alcohol (2-Propanol) (67-63-0)

Methanol (67-56-1)

Water (7732-18-5)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

F; R11

Full text of R-phrases: see section 16

15.2.2. National regulations

Ethyl Alcohol, 70% v/v

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ethanol (64-17-5)

Listed on IARC (International Agency for Research on Cancer)

Isopropyl Alcohol (2-Propanol) (67-63-0)

Methanol (67-56-1)

Water (7732-18-5)

15.3. US State regulations

Ethyl Alcohol, 70% v/v()

U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	Yes
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No

Ethanol (64-17-5)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

Isopropyl Alcohol (2-Propanol) (67-63-0)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

Methanol (67-56-1)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	Yes	No	No	

Water (7732-18-5)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

SECTION 16: Other information

Indication of changes : Revision - See : *.

Other information : None.

Full text of H-phrases: see section 16:


H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H301	Toxic if swallowed
H311	Toxic in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H331	Toxic if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H350	May cause cancer
H361	Suspected of damaging fertility or the unborn child
H370	Causes damage to organs

Ethyl Alcohol, 70% v/v

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
- NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.
- NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Hazard Rating

- Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given
- Flammability : 3 Serious Hazard
- Physical : 1 Slight Hazard
- Personal protection : D

SDS US ValTech

Information in this SDS is from available published sources and is believed to be accurate. No warranty, express or implied, is made and LabChem Inc assumes no liability resulting from the use of this SDS. The user must determine suitability of this information for his application.



ใบสำคัญการขึ้นทะเบียนตำรับยา
แผนปัจจุบัน
(ผลิต)

เลขทะเบียนที่ 1A 27/52

ใบสำคัญฉบับนี้แสดงว่า

ชื่อยา ETHYL ALCOHOL 70% ซาเอทิล แอลกอฮอล์

ตามแบบ ท.ย. ๑ เลขรับที่ 1A 427/50 เป็นชาชนิด น้ำใส สีฟ้าอ่อน

ผลิตโดย บริษัท ศิริบัญชา จำกัด

ใบอนุญาตเลขที่ 137/2526 อยู่เลขที่ 50/4 ตรอก/ซอย ศิริบัญชา

ถนน บางกรวย-ไทรน้อย หมู่ที่ 7 ตำบล/แขวง ไทรน้อย

อำเภอ/เขต ไทรน้อย จังหวัด นนทบุรี ประเทศ ไทย

ได้รับขึ้นทะเบียนไว้แล้ว

เมื่อวันที่ 30 เดือน มกราคม พ.ศ. 2552

ใบสำคัญการขึ้นทะเบียนตำรับยานี้มีอายุใช้ได้ตลอดเวลาที่ได้รับใบอนุญาตผลิตยาแผนปัจจุบัน

(นางรวีไล บอนรัตน์)
เภสัชชำนาญการพิเศษ
กองเภสัชกรรม

ผู้ปฏิบัติราชการแทนเลขาธิการคณะกรรมการอาหารและยา