

# tesaflex® 4169 PV3

Floor Marking Tape Premium

## PRODUCT INFORMATION

### Product Description

tesa® 4169 PV3 marking tape is UV resistant and due to the thick backing it is able to withstand high mechanical stress. It is perfect suitable for permanent marking applications.

### Main Application

- Marking of working areas e. g. in factories and warehouses.
- Guiding lines for mark sensitive vehicles e. g. transport robots.
- Marking of parking spaces and gangways in offices, hospitals, at fairs etc..

### Technical Data

■ Backing material	soft PVC	■ Adhesion to steel	1.8 N/cm
■ Total thickness	180 µm	■ Elongation at break	16.4 oz/in
	7.1 mils	■ Tensile strength	200 %
■ Type of adhesive	acrylic		30 N/cm
			17.1 lbs/in

### Properties

- |                                   |   |                               |   |
|-----------------------------------|---|-------------------------------|---|
| ■ Suitable for sensitive surfaces | + | ■ Suitable for rough surfaces | + |
|-----------------------------------|---|-------------------------------|---|

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

### Additional Info

The uni colors of tesaflex® 4169 PV3 are in accordance with the RAL color scheme.

For latest information on this product please visit <http://l.tesa.com/?ip=04169>

Page 1 of 1 / As of 03/21/15

#### tesa tape, inc.

5825 Carnegie Boulevard  
Charlotte, NC 28209  
Phone: 704 554 0707  
Toll Free: 800 426 2181  
Fax: 800 852 8831  
customer@tesatape.com

[www.tesatape.com](http://www.tesatape.com)

#### Technical Tape México S.A. de C.V.

Av. Santa Fe No. 170  
German Centre P 6-3-3Col.  
Lomas de Santa Fe  
Mexico D.F. C.P. 01210  
Phone: +52 (55) 5292 6978  
Fax: +52 (55) 5292 6977

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.