



NORM SPECIFICATION

EN ISO 20345:2022 (S1 PS FO SR)

Personal protective equipment - Safety footwear



EN 61340-5-1:2016

Electrostatics - Part 5-1: Protection of electronic devices from electrostatic phenomena - General requirements

DESCRIPTION

Safety sandal in a modern black-green color combination. The upper of the shoe is made of microfiber and perforated along its entire length. The non-slip sole made of two-density polyurethane ensures not only comfort, but also maximum security at every step. The shoes are equipped with a comfortable, perforated inner insole, which guarantees comfort and air circulation inside the shoe. The absorption of energy in the heel area absorbs shocks and reduces the feeling of foot fatigue. Thanks to the safety composite toe cap, the footwear meets the requirements of the EN ISO 20345: 2011 standard. This means that the feet are protected against compression with a force of up to 15 kN or the fall of a load of up to 20 kg from a height of 1 m. The feet are also protected from below, thanks to the composite antipuncture midsole. The shoes do not contain metal parts and are equipped with the ESD function. Therefore, it is an ideal model for indoor spaces and sensitive environments, where it is necessary to prevent sparks from electrostatic discharge or for rooms equipped with a safety frame. Thanks to the minimalist design, this model will fit perfectly with most Cerva workwear collections.



PRODUCT CODE - 02030116 XX YYY

Colours - XX

60 - black, light green

Sizes - YYY

034 - 34	035 - 35
036 - 36	037 - 37
038 - 38	039 - 39
040 - 40	041 - 41
042 - 42	043 - 43
044 - 44	045 - 45
046 - 46	047 - 47
048 - 48	049 - 49

COLOUR VARIANTS



60 - black, light green

MATERIALS

Antipuncture midsole material: composite
Upper material: microfiber
Toe cap material: composite
Outsole material: double density polyurethane
Lining material: polyester mesh

FEATURES

Shoes features: Energy absorption in heel area - E, Metal free - MF, Antislip outsole - SR, ESD - electrostatic discharge (EN 61340), Breathable upper, Antistatic shoes - A, Fuel and oil resistant outsole - FO, Antiperforation non-metallic midsole - PL, PS, Non-metallic safety toe cap - S
Profession: plasterboarder, warehouseman, production operator, driver
Application: plasterboarding, furniture moving
Industry: transport and storage, automotive
Area of usage: assembly room, maintenance
Half pair weight: 500 g

PACKAGING

Packaging type	Pieces in packaging	Size	Volume	Weight
CTN	10 PR	33 x 41.5 x 61.5 cm	84.224 dm³	13 kg
Pair	1 PR	0 x 0 x 0 cm	8422.4 cm³	1.3 kg

SIZE TABLES

Scan or Tap

