

# JABRA EVOLVE™ 65



## MORE THAN HEADSETS, A WORKPLACE EVOLUTION

- Made for voice calls and music
- Passive noise cancellation
- 30-meter (100 feet) wireless range
- 10-hour battery life



| DETAIL                           | INFORMATION  |
|----------------------------------|--|
| Packaging dimensions             | L 21.0 x W 18.1 x H 5.3 cm   |
| Weight mono / duo                | Mono headset 282.1 g, Stereo headset 310.3 g   |
| Whats in the box                 | Pouch, Evolve 65 Headset, Warning leaflet, Warranty leaflet, Quick Start Guide, Foam inlay (available for DUO only)  |
| Battery included                 | Yes  |
| Charging time                    | Max. 120 minutes   |
| AC power supply                  | USB power supply by PC with USB connection, Battery power with Bluetooth connection  |
| Certifications                   | Regulatory Approvals: CE, FCC ID, IC ID KCC, RCM, NCC, TELEC, SRRC<br>Industrial Certifications: Lync, Avaya, Cisco, Alcatel Lucent and Astra  |
| Warranty                         | 2 years  |
| Bluetooth device                 | Yes  |
| DECK Device                      | No   |
| NFC                              | No   |
| Operating range                  | Up to 30m/100ft  |
| Headset bandwidth                | Wideband   |
| Connection (mini jack, USB, etc) | USB/Bluetooth  |
| Talk time                        | Up to 7 hours  |
| Standby time                     | Up to 15 days  |
| Speaker Size                     | D28x3.9mm  |
| Speaker sensitivity              | 93.6dB SPL @1kHz   |
| Speaker impedance                | 32+/-4.8Ω, @1.0kHz   |
| Speaker Max Input Power          | Rated Input 5mW @0.4V, max input 10mW @0.56V   |
| Speaker Frequency Range          | 150Hz~7kHz, @Output S.P.L -10dB  |
| Microphone type                  | Electret Condenser (ECM) Uni-Directional Microphone  |
| Microphone Sensitivity           | f=1kHz, Pin=1Pa,0dB=1V/Pa Min: -32 dB, Max: -28 dB   |
| Microphone Frequency Range       | 100 Hz – 10 kHz  |
| Supported Bluetooth profiles     | A2DP (v1.2), Hands Free Profile (v1.6), Headset Profile (v1.2), AGHFP (v1.6)   |
| Bluetooth wireless technology    | Bluetooth 4.0  |
| Speaker bandwidth Music mode     | HiFi   |
| Speaker bandwidth Speak mode     | Wideband   |
| Microphone bandwidth             | Wideband   |
| Operating temperature            | -10 °C to + 50 °C  |
| Storage temperature              | -30 °C to + 80 °C Storage temperature range: (-20°C to +35°C 6 months), (+35°C to +45°C 3 months), (+45°C to +45°C 1 month), (+60°C to +70°C 1 hour with no degradation), (+70°C to +85°C max. 1 hour (<20% degradation) |
| Supported modes                  | SCO, eSCO, Sniff mode  |
| Security                         | Pairing, Authentication and Encryption (Bluetooth standard)  |
| Paired devices                   | Up to 8 trusted devices, 2 active stand-by Bluetooth connections   |
| Power consumption speaker        | Rated Input 5mW @0.4V, max input 10mW @0.56V   |
| Features                         | Busy Light, USB Controller, Discreet boom arm with magnet that integrates into the headset when not on calls, Connects to multiple devices (smartphone or tablet) with a 3.5mm jack                                      |

| SKU          | DESCRIPTION               | EAN CODE      |
|--------------|---------------------------|---------------|
| 6593-823-309 | Jabra EVOLVE 65 MS Mono   | 5706991017168 |
| 6599-823-309 | Jabra EVOLVE 65 MS Stereo | 5706991017144 |
| 6593-829-409 | Jabra EVOLVE 65 UC Mono   | 5706991017175 |
| 6599-829-409 | Jabra EVOLVE 65 UC Stereo | 5706991017151 |

\* Phone dependent