

Scotch® Removable Tape 811



General Description

A matte finish tape that features a unique adhesive that holds paper securely, yet is easy to remove or reposition. Great for layouts and temporary posting of papers, and you can write on it.

Catalog Number	Description
Scotch® Removable Tape 811	A matte finish tape that features a unique adhesive that holds paper securely, yet is easy to remove or reposition. Great for layouts and temporary posting of papers, and you can write on it. Available in 1/2" and 3/4" by 36 yard rolls and 1/2", 3/4" and 1" by 72 yard rolls.

Product Characteristic	*Average/Typical Values
Backing	Matte acetate
Adhesive	Acrylic (repositionable)
Tensile strength	13 lbs./in. width (ASTM D3759)
Total thickness	2.0 mils (ASTM D3811)
Plastic core	Polystyrene
Photo safe	Yes (per ISO Standard 18916)

*These are average values. 3M does not guarantee every roll will have these specific test values. Actual values may vary and may be greater than or less than the averages listed.

Features/Advantages/Benefits:

Feature (HAS)	Advantage (WHICH MEANS)	Benefit (SO THAT)
Unique adhesive	Removable, repositionable	Allows for correction and reuse without damage; can be removed from many surfaces
Acrylic adhesive	Long aging	Resists dry out, lasts a long time
Matte acetate backing	Can be written on with most pens, pencils, and markers	Makes the job easier when corrections are needed, can save time
Matte acetate backing	Easy to dispense	Convenient, can save time
Release coating	Smooth, easy unwind	Easy to pull tape off roll, easy to use
Blue plastic core	Clean appearance, identifies tape from other matte tapes	Customer convenience

Applications:

Scotch® Removable Tape #811 removes cleanly from most common office materials such as sulfite bond paper, 25% cotton bond paper, yellow legal paper, manila folders, 16# note paper and common office surfaces such as painted wallboard, wallpaper, finished woods, metals, plastics, and upholstery at normal office temperatures and humidity for a period of up to one year. If minor adhesive shedding should occur, the adhesive can be removed by:

1. Wiping with a dry Kleenex-type of product.
2. Low abrasion/soft rubber eraser, e.g., Rub Kleen #6002 - Eberhard Faber.
3. Window cleaner.
4. Rubbing alcohol.

Test removability before using. Avoid use in applications where clean removability from clay coated or specially treated papers is required. May not remove cleanly from some blueprint papers. May tear or pick fibers from loose bond papers such as newsprint, Kraft paper, and paper products not manufactured by the screen process.

This product is not suitable for packaging applications. Avoid applications on lacquered finishes, blackboards, CIBA chrome and other photographic paper, LEXAN plastic and leather.

All express or implied product claims are substantiated and approved for U.S. use only. If you intend to use any of the product features listed in any copy accompanying the product for any geographic location outside of the U.S., please consult with your local legal counsel.

NOTE: Best storage conditions are 70 degrees Fahrenheit and 50% relative humidity.

3M, Scotch and the Plaid Design are trademarks of 3M Company.

© 3M 2013

June, 2013