

---

# SAFETY DATA SHEET

Version 1.2  
Revision Date 12.08.2010

MSDS Number 30000015573  
Print Date 28.01.2013

---

## 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND THE COMPANY/UNDERTAKING

Product identifier : Mixture of Gases

Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : General Industrial

Restrictions on Use : No data available.

Details of the supplier of the safety data sheet : Air Products and Chemicals, Inc  
7201 Hamilton Blvd.  
Allentown, PA 18195-1501  
GST No. 123600835 RT0001  
QST No. 102753981 TQ0001

Email Address – Technical Information : GASTECH@airproducts.com

Telephone : 1-610-481-4911

Emergency telephone number (24h) : 800-523-9374 USA  
+1 610 481 7711 International

---

## 2. HAZARDS IDENTIFICATION

Classification according to Regulation 1272/2008 (CLP)

Gases under pressure - Compressed gas. H280:Contains gas under pressure; may explode if heated.

Label Elements according to Regulation 1272/2008 (CLP)

Hazard pictograms/symbols



Signal Word: Warning

Hazard Statements:

# SAFETY DATA SHEET

Version 1.2  
Revision Date 12.08.2010

MSDS Number 300000015573  
Print Date 28.01.2013

H280:Contains gas under pressure; may explode if heated.

## Precautionary Statements:

Storage : P410+P403:Protect from sunlight. Store in a well-ventilated place.

## Classification (Directive)

No EC labelling required.

## Other hazards

Distinctive rotten egg odor.  
Olfactory fatigue may lead to loss of this warning property.  
High pressure gas.  
Can cause rapid suffocation.  
Self contained breathing apparatus (SCBA) may be required.

## Environmental Effects

Not harmful.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance/Mixture : Mixture

Components	EINECS / ELINCS Number	CAS Number	Concentration (Volume)
Hydrogen sulphide	231-977-3	7783-06-4	25 PPM
Carbon monoxide	211-128-3	630-08-0	100 PPM
Methane	200-812-7	74-82-8	2.2 %
Oxygen	231-956-9	7782-44-7	18 %
Nitrogen	231-783-9	7727-37-9	> 79.78%

Components	Classification (Directive)	Classification (CLP)	REACH Reg. #
Hydrogen sulphide	F+ ; T+; N R12 ; R26 ; R50	Flam. gas 1 Press. Gas Acute Tox. Inha 2 Aquatic Acute 1	
Carbon monoxide	F+ ; T R61 ; R12 ; R23 ; R48/23	Flam. gas 1 Press. Gas Repr. 1A Acute Tox. Inha 3 STOT RE 1	
Methane	F+ R12	Flam. gas 1 Press. Gas	
Oxygen	O R 8	Ox. Gas 1 Press. Gas	

# SAFETY DATA SHEET

Version 1.2  
Revision Date 12.08.2010

MSDS Number 300000015573  
Print Date 28.01.2013

Nitrogen		Press. Gas	

If REACH registration numbers do not appear the substance is either exempt from registration, does not meet the minimum volume threshold for registration, or the registration date has not yet come due. Refer to section 16 for full text of each relevant R-phrase and H-phrases.

Concentration is nominal. For the exact product composition, please refer to Air Products technical specifications.

## 4. FIRST AID MEASURES

### Description of first aid measures

- General advice : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.
- Eye contact : Not applicable.
- Skin contact : Not applicable.
- Ingestion : Ingestion is not considered a potential route of exposure.
- Inhalation : Remove to fresh air. If breathing has stopped or is labored, give assisted respirations. Supplemental oxygen may be indicated. If the heart has stopped, trained personnel should begin cardiopulmonary resuscitation immediately. In case of shortness of breath, give oxygen.

### Most important symptoms and effects, both acute and delayed

- Symptoms : Exposure to oxygen deficient atmosphere may cause the following symptoms: Dizziness. Salivation. Nausea. Vomiting. Loss of mobility/consciousness.

### Indication of any immediate medical attention and special treatment needed

- Treatment : Hyperbaric oxygen is the most efficient treatment of carbon monoxide and dramatically reduces the biological half-life of carboxyhemoglobin. Although less effective, 100% oxygen by mask is useful if hyperbaric facilities are not available. Stimulant drugs are not indicated. Central nervous system toxicity may cause respiratory paralysis requiring assisted ventilation. Irritation of the deep lung may cause chemical pneumonitis and pulmonary edema.

## 5. FIRE-FIGHTING MEASURES

### Extinguishing media

- Suitable extinguishing media : All known extinguishing media can be used.
- Extinguishing media which must not be used for safety : No data available.

# SAFETY DATA SHEET

Version 1.2  
Revision Date 12.08.2010

MSDS Number 300000015573  
Print Date 28.01.2013

reasons.

**Special hazards arising from the substance or mixture** : Upon exposure to intense heat or flame, cylinder will vent rapidly and or rupture violently. Product is nonflammable and does not support combustion. Move away from container and cool with water from a protected position. Keep containers and surroundings cool with water spray.

**Advice for fire-fighters** : Wear self contained breathing apparatus for fire fighting if necessary.

**Further information** : No data available.

---

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures** : Evacuate personnel to safe areas. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Monitor oxygen level. Ventilate the area.

**Environmental precautions** : Do not discharge into any place where its accumulation could be dangerous. Prevent further leakage or spillage if safe to do so.

**Methods and material for containment and cleaning up** : Ventilate the area.

**Additional advice** : If possible, stop flow of product. Increase ventilation to the release area and monitor oxygen level. If leak is from cylinder or cylinder valve, call the Air Products emergency telephone number. If the leak is in the user's system, close the cylinder valve and safely vent the pressure before attempting repairs.

---

## 7. HANDLING AND STORAGE

### Precautions for safe handling

Protect cylinders from physical damage; do not drag, roll, slide or drop. Do not allow storage area temperature to exceed 50°C (122°F). Only experienced and properly instructed persons should handle compressed gases/cryogenic liquids. Before using the product, determine its identity by reading the label. Know and understand the properties and hazards of the product before use. When doubt exists as to the correct handling procedure for a particular gas, contact the supplier. Do not remove or deface labels provided by the supplier for the identification of the cylinder contents. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Use an adjustable strap wrench to remove over-tight or rusted caps. Before connecting the container, check the complete gas system for suitability, particularly for pressure rating and materials. Before connecting the container for use, ensure that back feed from the system into the container is prevented. Ensure the complete gas system is compatible for pressure rating and materials of construction. Ensure the complete gas system has been checked for leaks before use. Employ suitable pressure regulating devices on all containers when the gas is being emitted to systems with lower pressure rating than that of the container. Never insert an object (e.g. wrench, screwdriver, pry bar, etc.) into valve cap openings. Doing so may damage valve, causing a leak to occur. Open valve slowly. If user experiences any difficulty operating cylinder valve discontinue use and contact supplier. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety

# SAFETY DATA SHEET

Version 1.2  
Revision Date 12.08.2010

MSDS Number 300000015573  
Print Date 28.01.2013

relief devices. Damaged valves should be reported immediately to the supplier. Close valve after each use and when empty. Replace outlet caps or plugs and container caps as soon as container is disconnected from equipment. Do not subject containers to abnormal mechanical shocks which may cause damage to their valve or safety devices. Never attempt to lift a cylinder by its valve protection cap or guard. Do not use containers as rollers or supports or for any other purpose than to contain the gas as supplied. Never strike an arc on a compressed gas cylinder or make a cylinder a part of an electrical circuit. Do not smoke while handling product or cylinders. Never re-compress a gas or a gas mixture without first consulting the supplier. Never attempt to transfer gases from one cylinder/container to another. Always use backflow protective device in piping. When returning cylinder install valve outlet cap or plug leak tight. Never use direct flame or electrical heating devices to raise the pressure of a container. Containers should not be subjected to temperatures above 50°C (122°F). Prolonged periods of cold temperature below -30°C (-20°F) should be avoided.

## Conditions for safe storage, including any incompatibilities

Full containers should be stored so that oldest stock is used first. Containers should be stored in a purpose built compound which should be well ventilated, preferably in the open air. Stored containers should be periodically checked for general condition and leakage. Observe all regulations and local requirements regarding storage of containers. Protect containers stored in the open against rusting and extremes of weather. Containers should not be stored in conditions likely to encourage corrosion. Containers should be stored in the vertical position and properly secured to prevent toppling. The container valves should be tightly closed and where appropriate valve outlets should be capped or plugged. Container valve guards or caps should be in place. Keep containers tightly closed in a cool, well-ventilated place. Store containers in location free from fire risk and away from sources of heat and ignition. Full and empty cylinders should be segregated. Do not allow storage temperature to exceed 50°C (122°F). Return empty containers in a timely manner.

## Technical measures/Precautions

Containers should be segregated in the storage area according to the various categories (e.g. flammable, toxic, etc.) and in accordance with local regulations. Keep away from combustible material.

## Specific end use(s)

Refer to section 1 or the extended SDS if applicable

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Control parameters

#### Exposure limit(s)

Hydrogen sulphide	Time Weighted Average (TWA): EH40 WEL	5 ppm	7 mg/m <sup>3</sup>
Hydrogen sulphide	Short Term Exposure Limit (STEL): EH40 WEL	10 ppm	14 mg/m <sup>3</sup>
Carbon monoxide	Time Weighted Average (TWA): EH40 WEL	30 ppm	35 mg/m <sup>3</sup>
Carbon monoxide	Short Term Exposure Limit (STEL): EH40 WEL	200 ppm	232 mg/m <sup>3</sup>

If applicable, refer to the extended section of the SDS for further information on CSA.

### Exposure controls

#### Engineering measures

Provide natural or mechanical ventilation to prevent oxygen deficient atmospheres below 19.5% oxygen.

#### Personal protective equipment

Respiratory protection : Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmosphere.

# SAFETY DATA SHEET

Version 1.2  
Revision Date 12.08.2010

MSDS Number 300000015573  
Print Date 28.01.2013

	Air purifying respirators will not provide protection. Users of breathing apparatus must be trained.
Hand protection	: Sturdy work gloves are recommended for handling cylinders. The breakthrough time of the selected glove(s) must be greater than the intended use period.
Eye protection	: Safety glasses recommended when handling cylinders.
Skin and body protection	: Safety shoes are recommended when handling cylinders.
Special instructions for protection and hygiene	: Ensure adequate ventilation, especially in confined areas.
Remarks	: Simple asphyxiant.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Appearance	: Compressed gas.
Odor	: Not determined.
Odor threshold	: No data available.
pH	: Not applicable.
Melting point/range	: No data available.
Boiling point/range	: No data available.
Flash point	: Not applicable.
Evaporation rate	: Not applicable.
Flammability (solid, gas)	: No data available.
Upper/lower explosion/flammability limit	: No data available.
Vapor pressure	: No data available.
Water solubility	: No data available.
Relative vapor density	: No data available.
Relative density	: 0.9826 (air = 1) Lighter or similar to air.
Partition coefficient (n-octanol/water)	: Not applicable.
Autoignition temperature	: No data available.

# SAFETY DATA SHEET

Version 1.2  
Revision Date 12.08.2010

MSDS Number 300000015573  
Print Date 28.01.2013

Decomposition temperature : No data available.  
Viscosity : Not applicable.  
Explosive properties : No data available.  
Oxidizing properties : No data available.  
Molecular Weight : 28.46 g/mol

## 10. STABILITY AND REACTIVITY

Reactivity : Refer to possibility of hazardous reactions and/or incompatible materials sections  
Chemical Stability : Stable under normal conditions.  
Possibility of hazardous reactions : No data available.  
Conditions to avoid : No data available.  
Incompatible materials : No data available.  
Hazardous decomposition products : Sulphur compounds.  
Hydrogen.  
None.

## 11. TOXICOLOGICAL INFORMATION

### Information on toxicological effects

#### Likely routes of exposure

Effects on Eye : No adverse effect.  
Effects on Skin : No adverse effect.  
Inhalation Effects : In high concentrations may cause asphyxiation. Asphyxiation may bring about unconsciousness without warning and so rapidly that victim may be unable to protect themselves.  
Ingestion Effects : Ingestion is not considered a potential route of exposure.  
Symptoms : Exposure to oxygen deficient atmosphere may cause the following symptoms: Dizziness. Salivation. Nausea. Vomiting. Loss of mobility/consciousness.

#### Acute toxicity

Acute Oral Toxicity : No data is available on the product itself.

# SAFETY DATA SHEET

Version 1.2  
Revision Date 12.08.2010

MSDS Number 300000015573  
Print Date 28.01.2013

Inhalation : No data is available on the product itself.

#### Inhalation - Components

Hydrogen sulphide	LC50 (1 h) : 712 ppm	Species : Rat.
Carbon monoxide	LC50 (1 h) : 3760 ppm	Species : Rat.

Acute Dermal Toxicity : No data is available on the product itself.

Skin corrosion/irritation : No data available.

Serious eye damage/eye irritation : No data available.

Sensitization. : No data available.

#### Chronic toxicity or effects from long term exposures

Carcinogenicity : No data available.

Reproductive toxicity : No data is available on the product itself.

Germ cell mutagenicity : No data is available on the product itself.

Specific target organ systemic toxicity (single exposure) : No data available.

Specific target organ systemic toxicity (repeated exposure) : No data available.

Aspiration hazard : No data available.

---

## 12. ECOLOGICAL INFORMATION

### Toxicity

Aquatic toxicity : No data is available on the product itself.

Toxicity to other organisms : No data is available on the product itself.

### Persistence and degradability

No data available.

### Bioaccumulative potential

No data is available on the product itself.

#### Bioaccumulation - Components

Carbon monoxide	Does not bioaccumulate.
-----------------	-------------------------

# SAFETY DATA SHEET

Version 1.2  
Revision Date 12.08.2010

MSDS Number 300000015573  
Print Date 28.01.2013

## Mobility in soil

No data available.

## Results of PBT and vPvB assessment

If applicable, refer to the extended section of the SDS for further information on CSA.

## Other adverse effects

No data available.

---

## 13. DISPOSAL CONSIDERATIONS

Waste treatment methods : Contact supplier if guidance is required. Return unused product in original cylinder to supplier.

Contaminated packaging : Return cylinder to supplier.

---

## 14. TRANSPORT INFORMATION

### ADR

UN/ID No. : UN1956  
Proper shipping name : COMPRESSED GAS, N.O.S., (Nitrogen, Oxygen)  
Class or Division : 2  
Tunnel Code : (E)  
Label(s) : 2.2  
ADR/RID Hazard ID no. : 20

### IATA

UN/ID No. : UN1956  
Proper shipping name : Compressed gas, n.o.s., (Nitrogen, Oxygen)  
Class or Division : 2.2  
Label(s) : 2.2

### IMDG

UN/ID No. : UN1956  
Proper shipping name : COMPRESSED GAS, N.O.S., (Nitrogen, Oxygen)  
Class or Division : 2.2  
Label(s) : 2.2

### RID

UN/ID No. : UN1956  
Proper shipping name : COMPRESSED GAS, N.O.S., (Nitrogen, Oxygen)  
Class or Division : 2  
Label(s) : 2.2

Further Information

# SAFETY DATA SHEET

Version 1.2  
Revision Date 12.08.2010

MSDS Number 300000015573  
Print Date 28.01.2013

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. The transportation information is not intended to convey all specific regulatory data relating to this material. For complete transportation information, contact an Air Products customer service representative.

## 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Country	Regulatory list	Notification
USA	TSCA	Included on Inventory.
EU	EINECS	Included on Inventory.
Canada	DSL	Included on Inventory.
Australia	AICS	Included on Inventory.
Japan	ENCS	Included on Inventory.
South Korea	ECL	Included on Inventory.
China	SEPA	Included on Inventory.
Philippines	PICCS	Included on Inventory.

### Chemical Safety Assessment

Refer to extended SDS for CSA information

This product is either exempt from REACH, does not meet the minimum volume threshold for a CSA, or the CSA has not yet been completed.

## 16. OTHER INFORMATION

Ensure all national/local regulations are observed.

R-phrases - Components

R 8 Contact with combustible material may cause fire.

R12 Extremely flammable.

R23 Toxic by inhalation.

R26 Very toxic by inhalation.

R48/23 Toxic: danger of serious damage to health by prolonged exposure through inhalation.

R50 Very toxic to aquatic organisms.

R61 May cause harm to the unborn child.

Toxic to Reproduction Category 1

Hazard Statements:

H220 Extremely flammable gas.

H270 May cause or intensify fire; oxidiser.

H280 Contains gas under pressure; may explode if heated.

H330 Fatal if inhaled.

H331 Toxic if inhaled.

H360d May damage the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure

H400 Very toxic to aquatic life

Prepared by : Air Products and Chemicals, Inc. Global EH&S Product Safety Department

For additional information, please visit our Product Stewardship web site at

# SAFETY DATA SHEET

Version 1.2  
Revision Date 12.08.2010

MSDS Number 300000015573  
Print Date 28.01.2013

---

<http://www.airproducts.com/productstewardship/>

This Safety Data Sheet has been established in accordance with the applicable European Directives and applies to all countries that have translated the Directives in their national laws. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

---