

## Product Datasheet Safety Helmet airwing B with three variable ventilation zones



## UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth

Product characteristics	* size and weight optimised helmet
	* trendy design
	* variable air vents at the front and the back of the helmet
	* optimal fit, high wearing comfort
	* 6-point textile suspension harness optionally with wheel ratchet system
	* approved and labeled for use in temperatures as low as –30° C
	* side slots for attaching ear defenders or visors
	* suitable for head sizes of 51-61 cm
	resp. 52-61 cm (wheel ratchet system)
	* large printing areas

Technical details	
<b>Helmet shell</b> Material Weight	PE ca. 296 g
Interior	<ul> <li>* 6-point-textile suspension harness</li> <li>* headband made of high quality PE</li> <li>* circulating pad</li> <li>* easy to replace sweatband</li> <li>* medically shaped neck band to prevent slide on overhead working</li> </ul>
Versions	Conventional suspension harness
Weight	ca. 86 g
Colours / Art. No.	white 9762 020
	yellow 9762 120
	orange 9762 220 red 9762 320
	green 9762 420
	blue 9762 520
	black 9762 920
Weight	Suspension harness with wheel ratchet system for infinite width adjustment
Colours / Art. No.	ca. 98 g white 9762 030
	yellow 9762 130
	orange 9762 230
	red 9762 330
	green 9762 430
	blue 9762 530
	lime 9762 630
Packing	25 pieces / box
Standards	
Stallualus	DIN EN 397 in combination with EG-guideline 89/686/EWG