

## ge manyar

## Description

Twin edge Manyard with 45mm shock absorber

1028520 - 21 - 22 - 23References:

**Features** 

**Elastic webbing:** polyamide 45mm

**Breaking strength:** > 2200 daN



| Ref              | 1028523                                  | 1028522                                  | 1028520                              | 1028521                           |
|------------------|--|--|--------------------------------------|-----------------------------------|
| Length           | 1,5 m                                    | 2 m                                      | 1,5 m                                | 2 m                               |
| Leg ending       | 2 x Aluminium<br>Scaffhold Hook<br>65 mm | 2 x Aluminium<br>Scaffhold Hook<br>65 mm | 2 x Steel<br>Scaffhold Hook<br>55 mm | 2 x Steel<br>Scaffhold Hook 55 mm |
| Absorbeur ending | Aluminium Zicral<br>Twist Karabiner      | Aluminium Zicral<br>Twist Karabiner      | Steel CS20 Twist<br>Karabiner        | Steel CS20 Twist<br>Karabiner     |
| Weight           | 1,550 kg                                 | 1,580 kg                                 | 1,650 kg                             | 1,680 kg                          |
|                  |  |  |                                      |                                   |

EN354: 2002 / EN 355: 2002

## LAW of 19 MARCH 93

PPE are products classified in category III, mortal risks, and as such they have to be the object of a periodic inspection for less than twelve months at the time of its use by the qualified person.

For more information, please contact our technical team at 02 48 52 40 42 or by e-mail techniserv@sperian.com



Web site: www.sperianprotection.com