

### Product data sheet uvex silv-Air 3210 FFP2 NR D



#### Product information

<b>Product features</b>	<ul style="list-style-type: none"><li>• Particle-filtering flat fold mask with exhalation valve</li><li>• Protection level FFP2</li><li>• Soft material edges for high wearing comfort</li><li>• Continuous head band for a comfortable and secure fit</li><li>• Exhalation valve reduces breathing resistance and build-up of heat and moisture in the mask</li><li>• Flexible and adjustable nose clip</li><li>• Soft sealing lip guarantees a secure, comfortable sealed position of the mask</li><li>• The masks are individually packed</li><li>• Compatible with uvex safety eyewear</li><li>• Mask fulfils the requirements of the dolomite dust test (D)</li></ul>
<b>Materials</b>	Headband: textile Nose clip: PP Headband clips: PP Filter/mask: Melt Blown PP, Polyester Sealing lip: EVA foam Valve: ABS
<b>Weight</b>	14 g
<b>Standard</b>	EN 149:2001 + A1:2009

#### Versions

Article number	Colour/Version	Retail unit
8733.210	Flat fold mask FFP2, white with valve	15 pcs. per box
8753.210	Flat fold mask FFP2, white with valve	3 pcs. per bag

#### Packaging sizes

Box	approx. 200 x 140 x 140 mm
Outer Carton	approx. 540 x 440 x 230 mm

### Maximum breathing resistance acc. to EN149 in mbar

	Inhalation resistance 30l/min.	Inhalation resistance 95l/min.	Exhalation resistance 160l/min.
FFP1	0,6	2,1	3,0
<b>FFP2</b>	<b>0,7</b>	<b>2,4</b>	<b>3,0</b>
FFP3	1,0	3,0	3,0

### Areas of use\*

The respiratory protection mask can be used against solid, aqueous and non-volatile liquid aerosols up to <b>10 times</b> the respective limit values.	Woodworking, softwood, cement, metal, smog, fine dust, concrete, iron dust, ash, cotton dust, fluoride, carbon fibres, gypsum, fibre glass, copper, nickel, soot, pollen, house dust, pet hair.
--	---

\*Please note that the above mentioned areas of use are examples only. The selection of PPE needs to be carried out by a competent person, in conjunction with relevant and current legislation.

All respiratory protective devices fall into PPE category III (high risks).

Uvex accepts no liability for any possible harm or damage which may result from this information.  
This data sheet does not replace a detailed risk assessment nor seeking specialist advice.

UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth