

Technical Specifications

Lanyard

Description: Manyard complete with 2 galvanized connectors, with elastomer webbing.

Ref.	Max. length	Elasticity	Contracted length
1005317	1.5 m	29,7 %	1,05 m
1005318	2.0 m	32,5 %	1,35 m

Features:

Webbing with integrated shock absorber:

Raw material: Polyester fibers

Fall arrest force: < 500 daN

Ext. Tubular webbing:

Material: Polyamide green webbing 45mm, Teflon finish

Breaking strength: >2500 daN

Karabiners:

Material: Galvanized steel

Standard: EN362

Opening: 17 mm

Breaking strength: >2200 daN

Weight:

1005317:0.620kg

1005318:0.675kg

Breaking strength: >15KN

Temperature of use: -30°C to + 50°C

EN355 Shock absorber

**LAW of 19 MARCH 93**

PPE are products classified in category III, mortal risks, and as such they have to be the object of a periodic inspection for less than twelve months at the time of its use by the qualified person.

For more information, please contact our technical team at 02 48 52 40 42 or by e-mail techniserv.hsp@honeywell.com

HONEYWELL FALL PROTECTION FRANCE SAS

35-37 rue de la Bidauderie

F - 18100 Vierzon - France

Tel : +33 2 48 52 40 40

Fax : +33 2 48 71 04 97

Web site : www.honeywellsafety.com