



TAKTIK TS25 RTS ACTIV1

TAKTIK TS25 RTS ACTIV1 VL9035 SH

Features and functions

Mechanism:	ACTIV1: synchronous		
	Free floating:	Yes	
	Synchronised tilting of backrest and seat:	19° (backrest) i 8° (seat)	
	Backrest height adjustment:	Up&Down (10 ratchets)	
	Backrest and seat lock:	in 5 positions	
	Seat height adjustment:	with a pneumatic lift	
	Anti-Shock:	yes	
	Backrest tilt force adjustment:	with a knob located on the right side of the seat	
Backrest:	Upholstered, plastic cover		
	Backrest - foam:	thickness: 60 mm, density: 21 kg/m³	
	Backrest - construction:	polyprpylene (PP)	
Seat:	Upholstered		
	Seat - construction:	9 - layer beech plywood, thickness: 10,5 mm	
	Seat - foam:	thickness: 55 mm, density: 40 kg/m³	
Backrest height adjustment:	Yes		
Armrests:	None		
Base:	TS25-BL: Ø 710 mm, 5-star, black polyamide		
1	Base material:	plastic (PA+GF), black	
	Base type:	5-star	
	Base dimension:	Ø 710 mm	
Ø 50 Castors:	SH: Ø 50 mm, for soft floors, self-braking		
	Cut		



Backrest foam: Cut



Packaging: Box - 1 items

Dimensions

Total height:	995-1195 mm
Seat height:	380-510 mm
Backrest height:	625-695 mm
Seat width:	480 mm
Backrest width:	455 mm
Total depth:	644 mm
Seat depth:	400 mm
Seat surface depth:	455 mm
Backrest length:	535 mm

Finishes

Price group:	2	
Upholstery group:	Valencia	
	Flammability:	DIN 4102 B2
		EN 1021-1
		EN 1021-2
		NF P 92-503 M2
		Önorm A 3800-1 Q1
		Önorm B 3825
	Abrasion resistance:	300 000 Martindale cycles
	Colour fastness to light:	EN ISO 105-B02 (5)
	Others:	EN 71-3 safety of toys (migration of certain elements)
		PERMABLOK3® - superior antibacterial, antistain and antifungal protection
	Weight:	650g/m2
	Composition:	upper layer: 100% vinyl, bottom layer: 100% Hi-Loft polyest



Certifications

Certifications: Technical regulations, approvals and quality marks (for selected product configurations)

VL9035

Remodex (durability certificate) - approvals : EN 1335, EN 1022,