

tesa® 4195 PV2

High performance carton sealing tape

tesa® 4195 PV 2 is based on a PP backing with a special high tack water based acrylic adhesive mass. The excellent tack of the adhesive secures a good sealing immediately after applying it. Even tight packed boxes can be closed safely due to the good holding power and adhesive value.

The product has the following additional features:

- It offers a low noise unwinding
- It has a very good ageing and high temperature resistance for long storage times
- It can be used on all common hand dispensers and machines
- It can withstand comparably high storage temperature

As the product is chlorine free and based on derivatives of mineral oil only, the disposal by heat treatment is environmental friendly.

The process of cardboard waste recycling will be not disrupted as confirmed by leading recycling companies and paper mills.

Main Application

Manual and automatic sealing of medium-range weight cartons.

Technical Data

▪ Backing material	PP film	▪ Adhesion to steel	3 N/cm
▪ Total thickness	60 µm	▪ Elongation at break	140 %
▪ Type of adhesive	acrylic	▪ Tensile strength	55 N/cm

Properties

▪ Automatic application	yes	▪ Low noise unwinding	yes
▪ Manual application	yes		

Additional Information

The PV3-version of the product is printable. Available colours: havana and transparent.

For latest information on this product please visit <http://l.tesa.com/?ip=04195>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.