

CARATTERISTICHE HARDWARE

Interfaccia	4 10/100/1000Mbps RJ 45 LAN Ports 1 10/100/1000Mbps RJ 45 WAN Port 3 RJ11 Ports (1 DSL Port + 2 FXS Ports) 1 USB 2.0 Port
Tasto	WPS Button, Wi-Fi Button, Reset Button, Power On/Off Button
Alimentazione	12V/1.5A
Standard wireless	IEEE 802.11a/n/ac 5GHz, IEEE 802.11b/g/n 2.4GHz
Standard IEEE	IEEE 802.3, IEEE 802.3u, 802.3ab
Standard VDSL2	ITU-T G.993.2, Up to 30a profile (POTS) ITU-T G.993.5 (G.vector) ITU-T G.998.4 (G.INP)
Standard ADSL	Full-rate ANSI T1.413 Issue 2, ITU-T G.992.1(G.DMT), ITU-T G.992.2(G.Lite),
Standard ADSL2	ITU-T G.992.3 (G.DMT.bis), ITU-T G.992.4 (G.lite.bis)
Standard ADSL2+	ITU-T G.992.5 Annex A/M
Dimensioni (L x P x A)	214* 144.5*80 mm
Tipo di antenna	Internal antennas
Guadagno antenna	2dBi for 2.4G/3dBi for 5G

CARATTERISTICHE WIRELESS

Frequenza	2.4GHz and 5GHz (no DFS)
Signal rate	867Mbps at 5GHz, 300Mbps at 2.4GHz
Potenza di trasmissione	2.4GHz <20dBm 5GHz <23dBm
Funzionalità wireless	Enable/Disable Wireless Radio, WDS Bridge, WMM, Wireless Statistics
Sicurezza wireless	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA-PSK2 encryptions

CARATTERISTICHE SOFTWARE

QoS (Quality of Service)	Bandwidth Control
Sicurezza	NAT Firewall, Access Control, IP and MAC Address Binding
Modalità operative	VDSL2 Modem Router Wireless Router 3G/4G Router
Gestione	Web based configuration(HTTP) SNMP v1/v2c CWMP(TR-069)
DHCP	Server, Client, DHCP Client List, Address Reservation, DHCP Relay
Port forwarding	Virtual Server, Port Triggering, DMZ, ALG, UPnP
Dynamic DNS	DynDns, NO-IP

CARATTERISTICHE SOFTWARE

VPN pass-through	PPTP, IPSec Passthrough
Protocolli	Supports IPv4 and IPv6
Protocolli ATM/PPP	ATM Forum UNI3.1/4.0, PPP over ATM (RFC 2364), PPP over Ethernet (RFC2516), IPoA (RFC1577/2225), MER/IPoE (RFC 1483 Routed), Bridge (RFC1483 Bridge), PVC – Up to 8 PVCs
Funzionalità avanzate	Parental Control, Network Address Translation(NAT), Port Mapping(Grouping), Static Routing, RIP v1/v2(optional), DNS Relay, DDNS, IGMP V1/V2/V3
Condivisione USB	Support Samba(Storage)/FTP Server/Media Server, 3G/4G Modem
VPN IPsec	Supports up to 16 IPsec VPN tunnels

ALTRO

Certificazione	CE, RoHS
Contenuto della confezione	DSL VoIP Modem Router Archer VR1200v External Splitter RJ11 DSL Cable RJ45 Ethernet Cable Power Adapter Quick Installation Guide
Requisiti di sistema	Nessuno
Ambiente	Operating Temperature: 0°C~40°C Storage Temperature: -40°C~70°C Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing