

## CARATTERISTICHE HARDWARE

<b>Tipo di connettore</b>	EU, UK, US
<b>Standard e protocolli</b>	IEEE802.11ac, IEEE 802.11n, IEEE 802.11g, IEEE 802.11a, IEEE 802.11b
<b>Interfaccia</b>	1 * 10/100M Ethernet Port (RJ45)
<b>Tasto</b>	WPS Button, Reset Button
<b>Consumo energetico</b>	7.3W (max power consumption)
<b>Dimensioni ( L x P x A )</b>	3.1*3.0*3.0 in. (80*78*77mm)
<b>Antenna</b>	2* external

## CARATTERISTICHE WIRELESS

<b>Frequenza</b>	2.4GHz & 5GHz(11ac)
<b>Signal rate</b>	5GHz:Up to 867Mbps 2.4GHz:Up to 300Mbps
<b>Sensibilità di ricezione</b>	5GHz : 11a 6Mbps:-91dBm@10% PER 11a 54Mbps: -74dBm@10% PER 11ac HT20 mcs8: -68dBm@10% PER 11ac HT40 mcs9: -63dBm@10% PER 11ac HT80 mcs9: -59dBm@10% PER 2.4GHz 11g 54M: -79dBm@10% PER 11n HT20 mcs7: -77dBm@10% PER 11n HT40 mcs7: -74dBm@10% PER
<b>Modalità wireless</b>	Range Extender/Access Point Wireless Statistic Concurrent Mode boost both 2.4G/5G Wi-Fi band Wireless Statistic Concurrent Mode boost both 2.4G/5G Wi-Fi band
<b>Funzionalità wireless</b>	Access Control LED Control Domain Login Function
<b>Sicurezza wireless</b>	64/128-bit WEP WPA-PSK / WPA2-PSK
<b>Potenza di trasmissione</b>	<17dBm(2.4GHz) <17dBm(5GHz)

## ALTRO

<b>Certificazione</b>	CE, FCC, RoHS
<b>Contenuto della confezione</b>	AC1200 Wi-Fi Range Extender RE305 Quick Installation Guide
<b>Dimensioni scatola ( L x P x A )</b>	6.15*4*3.7in. (156.5*101.5*95mm)
<b>Requisiti di sistema</b>	Microsoft® Windows® 98SE, NT, 2000, XP, Vista or Windows 7, 8, 10, Mac® OS, NetWare®, UNIX® or Linux. Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F)
<b>Ambiente</b>	Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing

