

Technical description

INTRATA O-13-TS25-RTS-FS-SH

Description



- Office swivel chair with the upholstered seat and mesh backrest
- Seat UPH:
Structure is made of 7-layer plywood, thickness 10.5 mm, covered with two layers of cut foam, thickness 25 mm, density 35 kg/m³ and thickness 20 mm, density 40 kg/m³. Seat cover is made of black polypropylene (PP). Stitching on the seat to eliminate excessive upholstery stretching.
- Backrest MESH:
Structure is made of 6-layer plywood, thickness 9 mm, covered with cut foam, thickness 35 mm, density 35 kg/m³. Backrest cover is made of black polypropylene (PP).
- Base TS25:
Five star black polyamide, fi 710 mm
- Castors SH
Self-braking castors for soft floors (SH) as standard or for hard floors SHH as an option.

Dimensions



Basic dimensions:

- Total height adjustable in range: 1000-1130 mm
- Seat height adjustable in range: 425-555 mm
- Backrest height: 590 mm
- Seat width: 480 mm
- Seat depth: 440 mm

Features and functions



FS synchronous mechanism- functions:

- free floating – synchronous backrest and seat tilt
- backrest tilt angle of (20°) synchronised with the seat tilt angle (11°)
- seat and backrest multilock in lock in 5 positions
- backrest tilt force adjustment with a knob
- Smooth height adjustment of chair with pneumatic gas lift
- Anti-Shock- a feature that controls chair backrest to avoid hitting user's back after releasing the lock

Certificates



- Safety certificates: EN 1335
- GS Mark

Warranty:



- 5 years of warranty for the whole product
-