



TECHNICAL DATA SHEET

Mail Lite Tuff

Sealed Air Verpackungen GmbH

FEATURES

Mail Lite Tuff

COMPOSITION

2 sites white Polymate film and 2 sites bubble film

Color	white with black print
Middle weight Polymate Film	65 μ
Storage temperature	5°C – 50°C
Thermal decomposing	>360°C
Bubble diameter	9,5 mm
Bubble high	2,7mm
Tolerance	+/- 10%
Weight Air Cap EL Top HD	39 g/m ²
Tolerance	+/- 5%
Glue on the flap	Hot melt BAM 1474
The slide on the flap is permanent	
Pressure test: The welds on the mailers keep an internal pressure > 0.35 bar	

Outside dimensione
whidth
längth

A	B	C	D	E	F	G	G	H	J	K	CD
		170	200	240	240		260	290		370	200
		220	270	270	340		340	370		480	170

Mechanic resistance

Norm: DIN 53455

Tear strength across.....not tested

Tear strength lengthwisenot tested

Resiliencenot tested

Melt index bubble film ISO 1133 (190° - 2,16kg)0,92 g / 10min

★ ★ ★ ★ ★

Mail Lite Tuff mailer are 100% recyclable

★ ★ ★ ★ ★

NOTE:

The data in this data sheet are meant as guideline. A legally binding effect cannot be derived from it.

Created: 04.03.2010 AJ
Changed: 26.11.2015 AJ