



Private Label Transparent tape

Technical Datasheet

Version 1, December 2006

Description

A yellow general purpose transparent tape.

Characteristics

Backing	Bi-oriented polypropylene film
Dimensions	33m or 66 m rolls
Adhesive	Hot Melt Rubber resin
Adhesion to steel	5.00 N/cm
Tensile strength	2.4 daN/cm
Elongation at break	40 %
Film thickness	0.028 mm
Total thickness	0.048 mm

Above values are indicative values and should not be used as specifications.

FAB's (Features / Advantages / Benefices)

Feature (HAS)	Advantage (WHICH MEANS)	Benefit (SO THAT)
Synthetic Rubber resin adhesive	Aggressive adhesion to a variety of surfaces.	Eliminates the need for multiple tapes for the office.
Bi-oriented Polypropylene backing	Thin	Items taped together are not bulky, helps keep a professional look.
	Extruded film	Non-solvent process. Fewer emissions released into the atmosphere during processing.
	Easy tear (done through slitting)	Makes the job to tear by hand easier
Plastic core	Clean appearance.	Eliminates paper fragments on the edge of the roll and give a professional appearing tape application.
	Helps eliminate telescoped rolls.	Saves money, not having to throw away tape that is not useable.

APPLICATIONS:

General sealing applications: closure of small packages.