



## TEGERA® 12910

Chemical protection glove, PVC (Vinyl), seamless, cotton, sandy finish, Cat. III, blue, extra long, for heavy work

### PROPERTIES

Highest level of protection, very durable, good fit

### SPECIFICATION

TYPE OF GLOVE Disposable and/or chemical resistant gloves

CATEGORY Cat. III

SIZE RANGE (EU) 7, 8, 9, 10, 11

LINER MATERIAL Seamless, cotton

MATERIAL PVC (Vinyl)

DEXTERITY 5

GRIP PATTERN Sandy finish

LENGTH RANGE 700 mm

COLOUR Blue

PAIRS PER PACKAGE/CARTON 6/36

AQL 0.65

OUTER MATERIAL SPECIFICATION Polyvinyl chloride 100%


INNER MATERIAL SPECIFICATION Cotton 100%

SIZE	ART. NO.	EAN NO.
7	12910-7	
8	12910-8	
9	12910-9	
10	12910-10	
11	12910-11	

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.



CE 0075 Cat. III



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2017-04-24

## TEGERA® 12910

### FEATURES

Protection against chemicals, extra long

### PRIMARY PROTECTION

Risk of infection, corrosive injuries, contact with dirt, contact with chemicals, contact with moisture, contact with damp, contact with oil and fat

### PRIMARY ENVIRONMENTS OF USE

Chemical risk environments, microbiological risk environments, environments hazardous to health, corrosive environments, wet environments, moist environments, oil and greasy environments, dirty environments

### PRIMARY AREAS OF USE

HVAC installation, marine work, fishing industry work, petrochemical work, chemical work, chemical technology work, laboratory work, paper industry work, decontamination, sanitation, cleaning

### PRIMARY INDUSTRIES OF USE

Agriculture, oil, gas, petrochemical, pulp and paper, chemical

### TYPE OF WORK

Heavy weight

2(4)

**ejendals**  
PROTECTING HANDS AND FEET

#### EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10


info@ejendals.com

order@ejendals.com

www.ejendals.com



CE 0075 Cat. III



## TEGERA® 12910

### EC TYPE EXAMINATION

Notified Body: 0075 CTC, 4 rue Hermann Frenkel, 69367 Lyon Cedex 07 France

### COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EN 388:2003 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
A) Resistance to abrasion (No. of revolutions)	4	(4)
B) Resistance to cutting (Index)	1	(5)
C) Tear resistance (Newton)	2	(4)
D) Puncturing resistance (Newton)	1	(4)

EN 388 - Testing (specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
A) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	

EN 374-2:2003 Protective gloves against chemicals and micro-organisms - Part 2: Determination of resistance to penetration

EN 374-3:2003 Protective gloves against chemicals and micro-organisms - Part 3: Determination of resistance to permeation by chemicals

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com


www.ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2017-04-24



CE 0075 Cat. III



## TEGERA® 12910

Permeation levels are based on breakthrough times as follows

Permeation level	1	2	3	4	5	6
Minimum breakthrough times (min)	10	30	60	120	240	480

Definition of breakthrough time through the glove palm (1ugm/cm<sup>2</sup>/min)

A: Methanol (CAS Number 67-56-1) - Permeation level 2

J: n-Heptane (CAS number 142-85-5) - Permeation level 2

K: Sodium hydroxide 40% (CAS number 1310-73-2) - Permeation level 6

L: Sulphuric acid 96% (CAS number 7664-93-9) - Permeation level 3