# CONSTRUCT AND CIV

## **MASTERGUARD**

#### Certification

**Protective** properties

#### **DIN EN 397**

protective property down to −20 °C

internal equipment I/79 GY-R

6 point

with screw closure

possible

eco-leathe

4 point

1/79 GY

without screw closure

4 point

2

53-61cm

RAL 9016

RAL 1023

RAL 3020

■RAL 6024 RAL 2009

custom colours

printed (1)

HDPE (High-Density Polyethylene)

3

59-63cm

Side

 $9 \times 3 \text{ cm}$ 

 Protective property down to −30 °C integrated eye protection (only helmet I/79

• 16 mm double slots side ventilation (adjustable)

without side ventilation

hole in visor headtorch bracket cable loop

short visor all-round reflective film

face protection eye protection screen neck protection hearing protectionchin strap

sweat bands all-round reflective film

1

52-56cm

### Type Special feature Webbing Version Eye protection Sweat band Cushion strip

#### suspension Variant type

Chin strap

Version

Webbing

#### Series

- Factory fitted

- Accessories

- Size Head circumference Colours
- Branding

Item Size

Front  $4,5 \times 4,5 \text{ cm}$ 

parameter with extended neck section Shape

Weight

Material

approx. 365 g (1) printing just for 6 point webbing with screw closure

#### **APPLICATIONS**

- mainstream construction
- construction-related industries





#### Benefits

■ Protective property down to -20°C for use in low temperatures (e.g. outdoors in very cold



- Extensively proven construction safety helmet
- Large protective surface due to helmet with extended neck section



- Optional: Protective property down to -30°C For use in very low temperatures (e.g. cold storage
- Very comfortable to wear and secure fit due to ergonomically formed height-adjustable internal fittings
- side ventilation (adjustable)
- eco-leather sweatband
- rain gutter

