

Product Datasheet model i-vo 9160 265



UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth

<p>Product characteristics</p>	<ul style="list-style-type: none"> * Duo-spherical lens * Duo component technology * Extremely comfortable for all-day wear * Shock absorbing brow guard * Indirect ventilation * Quattroflex patented temple * Adjustable temple length and lens inclination
<p>Technical details</p> <p>Frame</p> <p>Material Colour</p> <p>Material Features Colour</p> <p>Material Features Colour</p>	<p>Front piece TPU/TPE blue/orange</p> <p>Side piece PA 5 position length adjustability blue</p> <p>Temple PBT+PC/TPE quattroflex temple blue/orange</p>

Manufacturer's ID code	Marking W
Applicable EN norm	166
Impact resistance	F (45 m/s)
Resistance to high speed particles at extremes of temperat.	T
Conformity symbol	CE
No. of certificat. body	0196
Lens	
Material	PC
Thickness	3 mm
Coating	supravisision HC-AF
Colour	clear
Filter	
Filter	2-1,2 (DIN EN 170)
Manufacturer's ID code	W
Optical class	1
Impact resistance	F (45 m/s)
Resistance to high speed particles at extremes of temperat	T
Surface resistance to fine particles	K
Antifog	N
Tested acc. to DIN	DIN
Conformity symbol	CE
Miscellaneous	
Weight	33 g
Packing	5 spectacles per box 200 spectacles per cardboard box
Standards	DIN EN 166 + DIN EN 170