SCHUBERTH

Technical datasheet SCHUBERTH® SHP 28-C

DESCRIPTION

Schuberth® SHP 28-C helmet mounted hearing protectors are suitable for environments that require the use of head protection in combination with hearing protection, such as, construction, forestry, oil & gas and heavy industry. SHP 28-C helmet mounted hearing protectors can be simply converted into a head, face and hearing protection combination



SHP 28-C				ba Participantes Participantes		Wei	ght: 2	267 g	Те	sted	to: E	N 3	52-3	:2002
Freq.kHz	0.063	0.125	0.250	0.5	1	2	3.15	4	6.3	8	H	M	L	SNR
Mean value	16.5	15.0	20.5	28.0	33.2	40.8	38.6	37.4	38.7	40.7				
1 std. deviation	6.0	5.0	4.7	4.5	4.3	3.8	3.2	3.6	2.9	3.2	34	25	17	28
APV	10.5	10.0	15.8	23.5	28.9	37.0	35.4	33.8	35.8	37.5				

MATERIAL DATA

Part	Material				
1. Attachment arm	POM				
2. Spring housing/helmet adapter	PA66				
3. Foam liner	Polyether				
4. Ear cup	ABS				
5. Ear cushion	Polyether & PVC foil				