

TAKTIK TS25 RTS ACTIV1

TAKTIK TS25 RTS ACTIV1 VL9035 SH




Features and functions

	Mechanism:	ACTIV1: synchronous
		Backrest height adjustment: Up&Down (10 ratchets)
		Seat height adjustment: with a pneumatic lift
		Synchronised backrest and seat tilt angle: 19° (backrest) i 8° (seat)
		Free floating: Yes
		Backrest tilt force adjustment: with a knob located on the right side of the seat
		Backrest and seat multilock: in 5 positions
		Anti-Shock - feature that controls backrest to avoid hitting user's back after releasing a lock: yes
	Backrest:	Upholstered, plastic cover
		Backrest - construction: polyprylene (PP)
		Backrest - foam: thickness: 60 mm, density: 21 kg/m³
	Seat:	Upholstered
		Seat - foam: thickness: 55 mm, density: 40 kg/m³
		Seat - construction: 9 - layer beech plywood, thickness: 10,5 mm
	Backrest height adjustment:	Yes
	Armrests:	None
	Base:	TS25-BL: Ø 710 mm, 5-star, black polyamide
		Base type: 5-star
		Base dimension: Ø 710 mm
		Base material: plastic (PA+GF), black
	Castors:	SH: Ø 50 mm, for soft floors, self-braking
	Seat foam:	Cut



Backrest foam: **Cut**



Packaging: **Box - 1 items**

Dimensions

Total height: **995-1195 mm**
 Seat height: **380-510 mm**
 Backrest height: **625-695 mm**
 Seat width: **480 mm**
 Backrest width: **455 mm**
 Total depth: **644 mm**
 Seat depth: **400 mm**
 Seat surface depth: **455 mm**
 Backrest length: **535 mm**

Finishes

Price group: **2**

Upholstery group: **Valencia**

Others: EN 71-3 safety of toys (migration of certain elements)

PERMABLOK3® - superior antibacterial, antistain and antifungal protection

Flammability: DIN 4102 B2

EN 1021-1

EN 1021-2

NF P 92-503 M2

Önorm A 3800-1 Q1

Önorm B 3825

Composition: upper layer: 100% vinyl, bottom layer: 100% Hi-Loft polyest

Abrasion resistance: 300 000 Martindale cycles

Weight: 650g/m2

Colour fastness to light: EN ISO 105-B02 (5)

Upholstery colour: **VL9035**



Certifications

Certifications: **Technical regulations, approvals and quality marks (for selected product configurations)**
Remodex (durability certificate) – approvals : EN 1335, EN 1022,