



Sir Safety System S.p.A. Single-member company Wholly-owned subsidiary of Sir Holding Srl Via dei Fornaciai, 9 - Santa Maria degli Angeli 06081 Assisi - Perugia - Italy Tel.+39 075.8043737 - Fax +39 075.8048686 VAT Nr. IT 03359340548 Viale Europa 74 20090 Cusago Milano Tel. +39 02.90394575 Fax +39 02.90394441 export@sirsafety.com www.sirsafety.com Quality Management System Certificate UNI EN ISO 9001:2015

Name: FACTOR ULTRA LIGHT SHOE

Code: MB2013Z9

**MB20 FOOTWEAR - ULTRA LIGHT SERIES** 

## Description

Dissipative shoe, low model, with a cutting-edge seamless upper in polyester mesh, abrasion and tear resistant. Metal free.

Fibreglass toecap and composite midsole with 4 mm-constant thickness. S1P.

SOLE: (EVA/RUBBER) Sole in highly expanded EVA material, with high anti-shock power, which makes the shoes more flexible and lighter. Outsole in nitrile rubber which assures perfect adhesion on either dry or wet surfaces. SRC slip resistant.

INSOLE: Insole made of two-component material with shell in polyurethane foam and memory PU having variable thickness: 4 mm at the front and 9 mm in the heel area. Considerable anti-shock properties. Antistatic.

DRY PLUS LINING: In polyester, with high draining power due to the high absorbing properties of the fabric and structure.



- Extremely lightweight, breathable and comfortable
- Seamless upper for better fit to the foot, tear and abrasion resistance
- High Durability Cap System: high durability TPU overcap system
- T-FLEX" composite midsole with constant thickness of 4 mm
- TPU rear support to optimize stability in the heel area
- Ergonomic and ultra-flexible Eva/rubber outsole that guarantees a high level of comfort
- Suitable for environments characterized by soils with low degree of roughness.

