

ELIPSE® HALF-FACE MASK with HESPA® + P3 (R) Nuisance Odour Filters Code SPR337 (S/M) and SPR502 (M/L), Filters SPR336

elipse



FILTER TECHNOLOGY

NFCS7/14

NFC House

Mellishaw Lane,

Morecambe, Lancs LA3 3EN

United Kingdom

Telephone: +44 (0)1524 847600

Fax: +44 (0)1524 847800

e-mail: elipse@gvs.com

Web site: www.gvs.com

DISTRIBUTED BY:



Avda. Santa Cruz, 36

39100 – Santa Cruz de Bezana

Cantabria (ESPAÑA)

Teléfono: +34 942 58 23 23

Fax: +34 942 58 23 24

e-mail: 3l@3linternacional.com

APPLICATION

Removal of dust, mist and fume of all types, and micro-organisms eg. bacteria & viruses.

FILTER TYPE/GRADE

HESPA+ P3 * >99.95%

FILTER CONSTRUCTION

Low profile design, close-pleated multi-layer HESPA® media and carbon element. Encapsulated with TPE, flexible frame easy to affix securely to mask.

MASK CONSTRUCTION

Mask: Blue TPE (thermoplastic elastomer), latex & silicone free, odour-free, non-allergenic material.

Valve Body: Nylon.

Inhalation/Exhalation Disk: Silicone rubber.

Elasticated head and neck strap.

Mask + Filters: 136 gm

WEIGHT

SHELF LIFE

5 years (mask & filters) See storage conditions on Instructions for Use and MSDS.

FILTER LIFE IN USE

>8 hours, re-usable

SAFETY FEATURES

Large non-return exhaust valve to reduce risk of wearer fatigue.

Low profile design HESPA® + filters offering wide field of vision.

Adjustable light weight head strap to ensure comfort and secure fit during use.

* Independently tested and Approvals given as follows:

Mask fully approved and CE certified to: EN140:1998

Filters fully approved and CE certified to: BS EN143:2000/A1 P3 (R)

PERFORMANCE DETAIL WITH HESPA® + P3 (R) FILTERS

BREATHING RESISTANCE				
	Resistance (mbar)			
	Inhalation			Exhalation
	30 l/m	95 l/m	160 l/m	160 l/m
	0.17	0.59	0.96	2.27
Max Permitted	0.5	1.3	2.00	3

INWARD LEAKAGE %	
With Hespas+	Mean
One size	0.18
Max Permitted	2

CO ₂ CONTENT	
Less than	0.1%
Max Permitted	2

EFFICIENCY	
HESPA+ P3 ®	>99.95%



Large non-return exhaust valve.

HESPA® + filter, Ultra low profile design, depth of visual filter on the mask : 5mm

Elasticated adjustable head and neck strap, secure & stable fit in use.

Dimensions

Filter: 12mm x 97mm x 53mm (widest point)

Mask: 93mm x 130mm x 110mm (widest point)

Weight:

Ultra Low-weight HESPA® + Filters Only: 19 gm each

Low-weight Elipse® mask: 98 gm



Inside – showing carbon element



HESPA® and Elipse® are trademarks of GVS. The pleat encapsulation filter technology used in this face mask is patented.

Issue 3

Issue Date: 08/04/15

ELIPSE® FACEMASK