



Cadeira de Operador PC10, preta



Descrição

Cadeira ergonómica de operador com destaque

- Mecanismo de contacto permanente
- Encosto e banco de tecido
- Assento ajustável em altura através de elevação a gás, inclinação das costas, ajuste manual da profundidade do

Uso Recomendado: Peso
Máximo Recomendado:

5 horas por dia
110kg

Garantia: 2 anos

Testado contra

EN 1335
BS 7176 – baixo risco

Acessórios Opcionais

Apoios de braço fixos ou ajustáveis em altura como

Apoios de braço fixos: 18.770.342
Apoios de braço ajustáveis 18.770.329

Dimensões do Produto

Product Dimension (as illustrated - in cm)				
Overall Width [W]	47	\		
Arms Inner Width [W1]	n/a	\		
Seat Width [W3]	47	\		
Seat Height [H2] (min/max)	42-54	\		
Seat Depth [D1]	42.5	\		
Back Width [W2]	45	\		
Back Height [H1]	50.5	Back height adjustment: 6cm		
Chair cushion Depth [D2]	54	\		
Arms Height [H3] from floor (min/max)	n/a	\		
Overall Depth [D]	57.5	\		
Overall Height [H] (min/max)	91.5-103.5	Included back height adjustment of 5cm	Overall Dimensions [D*W*H]	D57.5*W47*H91.5-103.5 CM



Materiais e Componentes

Material Name	Material Type	Fire Retardancy
Covering Materials (BACK)	Fabric 100% Polyester	BS7176 - low hazard
Covering Materials (SEAT)	Fabric 100% Polyester	BS7176 - low hazard
Foam Density (BACK)	25kg/cbm	BS7176 - low hazard
Foam Density (SEAT)	25kg/cbm	BS7176 - low hazard

Components	Material Type	Comments
Arms	(Optional: Polypropylene)	(Optional: Load capacity 45kg - 441 Newtons)
Mechanism	Steel	Permanent Contact Mechanism Initial angle for seat: 2° , Back angle: initial 8° (backwards), Maximum 20° (backwards)
GasLift	Steel	D120 black Sinking 10mm, class 3 Stroke 120mm, class 3
Base	Nylon	R320
Castors	Polypropylene	50/38 black castors

Informação Logística

Logistic Information	
Selling Unit of Measure	EACH
Number per Products per Carton	1
Carton Size (in cm)	65*32*58.5
Net Weight (in kg)	10
Gross Weight (in kg)	11.6