

## ecoLogo® Pegamento en cinta Permanente ®

tesa Roller ecoLogo® adhesivo permanente, la manera más moderna para obtener una adhesión de larga duración.

### Aplicación principal

- Adherencia extra fuerte, limpia y rápida
- Pega papel, cartón, fotos
- El color de la punta y la rueda indican su aplicación: rojo = adhesivo permanente
- Cinta de soporte más resistente (PET)
- Libre de disolventes
- 81% plástico reciclado, recarga 61% plástico reciclado (sin cinta)
- Embalaje: cartón reciclado, blíster libre de PVC

### Datos técnicos y Propiedades

<b>Dimensiones</b>	14m x 8.4mm, 8.5m x 8.4mm
<b>Color</b>	transparente
<b>Adhesivo</b>	Adhesivo Acrilato
<b>Packaging</b>	PP / PE / Cartón reciclado
<b>Material contenedor</b>	PS reciclado
<b>Almacenamiento</b>	Aprox. 2 años después de la apertura a una temperatura de entre 5-35 °C. Almacenar en un lugar seco.

For the latest information on this product please visit <http://www.tesa.com/consumer>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

## Información adicional e imágenes



59110

For the latest information on this product please visit <http://www.tesa.com/consumer>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.