

tesa Powerbond® Cinta Doble Cara – 55791, 55792

La cinta de montaje Ultra Fuerte tesa® de doble cara más fuerte es capaz de mantener en su lugar objetos pesados, tanto en interiores como en exteriores.

Es una alternativa perfecta al taladro. La tecnología tesa Powerbond®, junto con una adherencia de hasta 10 kg por 10 cm de tira, permite fijar de forma permanente incluso objetos muy pesados.

Aplicación principal

- Ideal para su uso en interiores y exteriores
- Sujeción fuerte
- Fija fuerte en superficies lisas y firmes
- No resistente a los rayos UV. Proteger del contacto directo con agua.
- Para objetos planos con un espesor de hasta 10mm y en superficies lisas y firmes.

Datos técnicos y Propiedades

Dimensiones	55791 – 1,5m : 19mm 55792 – 5m : 19mm
Espesor	1,1 mm
Adhesivo	Caucho sintético
Revestimiento	Papel siliconado de doble cara
Tiempo de almacenaje	1 año (en caja cerrada)
Temperatura	Temperatura óptima de montaje: 20 – 25° (mínimo 10 °C)
Poder de sujeción	Soporta hasta 10kg por cada 10cm de cinta

For the latest information on this product please visit <http://www.tesa.com/consumer>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

Información adicional e imágenes



55791



55792

For the latest information on this product please visit <http://www.tesa.com/consumer>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.