

3M Construction & Home Improvement Markets

Product Information Sheet

Issue : November 2018

Scotch Strong/ Indoor Mounting tape

Ref 40011915 - 40011950



Description

Scotch® Strong/Indoor Mounting Tape is a double-coated foam tape designed for permanently fixing small to medium items to most surfaces inside your home

Product Characteristics	
Backing	Polyethylene foam
Adhesive	Rubber
Standard Roll length	40011915 : 1.5 m 40011950 : 5 m
Color	White

Typical Physical Properties	value	Method
Total thickness	0.8 mm	ASTM D-3652
Density	95 kg / m ³	
Weight claim	1kg / 30 cm Max item weight 4.5 kg	Internal method
Surfaces	Finished & Painted Surfaces, Metals, Tile, Other Hard and Smooth Surfaces	Internal method
Temperature Application	10°C to 40°C	

The values displayed are the result of illustrative lab test measures made according to the indicated test method and shall not be considered as a commitment from 3M

Storage

To obtain best performances, store this product under normal condition of 21°C and 50% relative humidity in the original packaging and use it within one year from date of purchase.

3M Construction & Home Improvement Markets

Product Information Sheet

Application

Application temperature is 10°C – 38°C. Bond strength is dependent upon the amount of adhesive - to -surface contact developed. Firm application pressure helps develop better adhesive contact and improve bond strength. Entire tape surface must adhere completely to both sides

To obtain optimum adhesion, the bonding surfaces must be clean, dry and free of dust. Typical surface cleaning solvent are rubbing alcohol or water. Do not use household cleaners.

This is a permanent tape and may cause damage if removed. Do not use on delicate or curved surfaces, or areas where injury might occur if mounted object fell. Ensure that surface is strong enough to hold mounted object.

Important notice :

The use of the 3M product described within this document assumes that the user has read and understood the user notice. Before any use of this product it is recommended to complete some trials to validate the performance of the product within its expected purpose.

All information and specification details contained within this document are inherent to this specific 3M product and would not be applied to other products or environment. Any action or usage of this product made in violation of this document is at the risk of the user.

Compliance to the information and specification relative to the 3M product contained within this document does not exempt the user from compliance with additional guidelines (safety rules, procedures). Compliance to operational requirements especially in respect to the environment and usage of tools with this product must be observed. The 3M group (which cannot verify or control those elements) would not be held responsible for the consequences of any violation of these rules which remain external to its decision and control.

Warranty conditions for 3M products are determined with the sales contract documents and with the mandatory and applicable clause, excluding any other warranty or compensation