

tesa® Cinta Antideslizante Fluorescente – 55580

La cinta antideslizante Anti-Slip Tape de tesa® es un medio inteligente y eficaz para prevenir las caídas en peldaños de escaleras, rampas, suelos resbaladizos o cascos de barcos. Ayuda a prevenir accidentes y es sinónimo de adhesión fuerte y duradera. También protege de los rayos UV y es muy resistente al agua, las temperaturas extremas y a los productos de limpieza. Un paquete contiene 5 o incluso 15 m de cinta la cual es o bien 25 o 50 mm de ancho y está disponible en tres colores. Puede cortar la cinta o rasgarla con la mano para que coincida con una situación específica.

Aplicaciones Principales

- Para aplicaciones en interiores y exteriores
- Cinta extramadamente fuerte y duradera
- Muy fuerte adhesión
- Desgarrable a mano
- Resistente al agua salada, a los rayos UV y a los productos de limpieza
- Certificado según DIN 51130 con nivel antideslizante de R13 (mejor en su clase)

Datos técnicos y Propiedades

Dimensiones	5m x 25mm
Color	Fluorescente
Espesor total	850 µm
Soporte	PVC
Tipo de adhesivo	Acrílico
Adhesión sobre el acero	10 N/cm
Resistencia a la temperatura	-5°C a +50°C
Elongación a la rotura	200%
Desgarrable a mano	●●●
Resistencia al agua salada	●●●
Resistencia a los productos químicos	●●●

Evaluation across relevant tesa® assortment: ●●●● Muy bueno ●●● Bueno ●● Medio ● Bajo

For the latest information on this product please visit <http://www.tesa.com/consumer>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

Información adicional e imágenes



55580

For the latest information on this product please visit <http://www.tesa.com/consumer>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.