

SAFETY JOGGER

INDUSTRIAL

CLASSICS

BESTBOY S3

All-time favorite, mid-cut safety shoe

All-time favorite, mid-cut safety shoe, with all features of the original bestboy in an updated design.

Upper	Barton Action Leather
Outsole	PU/PU
Toecap	Steel
Midssole	Steel
Lining	Mesh
Footbed	SJ foam footbed
Safety category	EN ISO 20345 - S3 / SRC
Sample weight	0.710 gr.
Size range	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 / CM 23.0-31.5



OIL & FUEL RESISTANT

The outsole is resistant against oil and fuel.



S3

S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.




SRC SLIP RESISTANCE

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



STEEL TOECAP

Robust metal support to protect the feet of the wearer against falling or rolling objects.



STEEL MIDSOLE

Puncture resistant steel midsoles are made from stainless or coated steel and prevent sharp objects from penetrating the outsole.



BREATHABLE LEATHER UPPER

Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.

SAFETY JOGGER

INDUSTRIAL

CLASSICS

BESTBOY S3

Industries:

Automotive, Chemical, Cleaning, Construction, Industry, Logistics, Oil & Gas

Environments:

Dry environment, Muddy environment, Uneven surfaces, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.



	Description	Measure unit	Result	EN ISO 20345
Upper	Barton Action Leather			
	Upper: permeability to water vapor	mg/cm ² /h	2.2	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	25	≥ 15
Lining	Mesh			
	Lining: permeability to water vapor	mg/cm ² /h	49.8	≥ 2
	Lining: water vapor coefficient	mg/cm ²	398.8	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance	cycles	400	≥ 400
Outsole	PU/PU			
	Outsole abrasion resistance (volume loss)	mm ³	56.4	≤ 150
	Outsole slip resistance SRA: heel	friction	0.37	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.34	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.14	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.18	≥ 0.18
	Antistatic value	MegaOhm	120.7	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	29	≥ 20
Toecap	Steel			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	≥ 14
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	≥ 14
	Impact resistance toecap (clearance after impact 200J)	mm	15	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	15	≥ 14

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Sample size:
41