



**Spill Station Australia Pty Ltd**

1 Blackfriar Pl  
Wetherill Park  
NSW 2164

www.spillstation.com.au

## SAFETY DATA SHEET

Issued 20th December 2022

### **SECTION 1 — PRODUCT IDENTIFICATION**

Product Name : General Purpose/Universal Absorbent

Intended Use: Universal sorbent

Company Details: Spill Station Australia Pty Ltd  
1-3 Blackfriar Pl  
Wetherill Park NSW 2164  
Ph: +61 2 9609 8700  
Email: info@spillstation.com.au

### **SECTION 2 – HAZARDS IDENTIFICATION**

Appearance: Non woven material

Odour, colour, grade: Grey, no odour

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO NOHSC AUSTRALIA

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG  
CODE

### **SECTION 3 — COMPOSITION**

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>% by Wt</u>
Surfactant	9036-19-5	<11
Pigment	Not listed	<1
Polypropylene	9003-07-0	>88



**Spill Station Australia Pty Ltd**

1 Blackfriar Pl

Wetherill Park

NSW 2164

[www.spillstation.com.au](http://www.spillstation.com.au)

#### **SECTION 4 — FIRST AID MEASURES**

Eyes :

If irritation occurs, flush eyes immediately with large amounts of water for at least 20 minutes and continue flushing until irritation subsides. If redness or irritation persists, contact a physician.

Skin :

No hazard in normal use.

If any irritation, flush with large amounts of water, use soap if available.

After contact with the molten product, cool rapidly with large amount of cool water to dissipate heat. Do not pull solidified product off the skin. Cover with clean cotton sheeting or gauze and get prompt medical attention no attempt should be made to remove material from skin to remove contaminated clothing, as the damaged flesh can be easily torn.

Inhalation :

N.A.

Ingestion :

N.A.

#### **SECTION 5 — FIRE & EXPLOSION HAZARD**

FLASHPOINT : > 250 degree C

FLAMMABLE LIMITS : N.A

AUTOIGNITION TEMPERATURE : 435 degree C

##### **GENERAL HAZARD**

Solid material, may burn at or above the flashpoint, and airborne dust may explode if ignited.

Toxic gases will form upon combustion.

##### **FIRE FIGHTING**

Use water spray to cool fire exposed surface and protect personnel.

Isolate "fuel" supply from fire.

Respiratory and eye protection required for fire fighting personnel.

##### **DECOMPOSITION PRODUCTS UNDER FIRE CONDITIONS**

Oxygen-lean conditions may produce carbon monoxide and irritating smoke.



## **SECTION 6 — ACCIDENTAL RELEASE**

Steps to be taken in case material is released or spilled : N.A.

## **SECTION 7 – HANDLING AND STORAGE**

### **HANDLING**

This product is considered to be an article which does not release or otherwise result in exposure to a hazardous chemical under normal use conditions.

### **STORAGE**

Keep dry.

Avoid storing near strong oxidizers.

Avoid sources of ignition.

Use caution when stacking to avoid unstable conditions.

Store at ambient temperature.

Store at atmospheric pressure.

Store in a sprinkler system warehouse.

## **SECTION 8- EXPOSURE CONTROLS/PERSONAL PROTECTION**

No precaution required for normal handling of this product.

## **SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES**

Form :	Fiber
Color :	Grey
Melting Point :	155-165 degree C
Specific Gravity ( Water = 1 ) :	0.91
Solubility in Water :	insoluble
Vapor Pressure ( Air = 1 ) :	N.A.
Vapor Density :	N.A.
Evaporation Rate :	N.A.
Hydrophilic	



**Spill Station Australia Pty Ltd**

1 Blackfriar Pl

Wetherill Park

NSW 2164

[www.spillstation.com.au](http://www.spillstation.com.au)

## **SECTION 10 — STABILITY AND REACTIVITY**

Stability : Stable

Hazardous Polymerization : N.A.

Hazardous Decomposition Products : None.

## **SECTION 11 — TOXICOLOGICAL INFORMATION**

### **Reported Human Effects**

No primary dermal irritation human patch tests have been carried out with this product.

### **Reported Animal Effects**

No animal toxicity studies have been carried out with this product.

## **SECTION 12 – ECOLOGICAL INFORMATION**

No data

## **SECTION 13 – DISPOSAL CONSIDERATIONS**

Dispose of in accordance with local, state and federal regulations.

## **SECTION 14 — TRANSPORTATION**

Hydrocarbon Absorbents are made with strict dimensional tolerance specifications. However, it is possible for the rolls to shift, shrink, or otherwise change dimensions to a maximum of +/-0.5% during handling or shipment.

## **SECTION 15 — REGULATORY INFORMATION**

No data

## **SECTION 16 — OTHER INFORMATION**

The information given in this data sheet is to the best of our knowledge, true and accurate, but any recommendations or suggestions that may be made are without guarantee, since the conditions of use are beyond our control. The information and recommendations offered are for the user's consideration and is the user's responsibility to satisfy them selves that they are suitable and complete for their purpose. We recommend that the safety and handling information presented in this data sheet be passed on, in an appropriate format, to your customers and handlers.