



EU-TYPE EXAMINATION CERTIFICATE



The following model of Personal Protective Equipment has been subjected to an EU-type examination in accordance with the module B of the PPE regulation (2016/425) and has been shown to satisfy to essential health and safety requirements.

Certificate N° 0075/1142/162/03/25/0563

Issued by CTC, Notified Body N°0075, to the following model of personal protective equipment :

Manufacturer : Intersafe Netherlands B.V.
Carrosserieweg 5, 3445 BC WOERDEN
THE NETHERLANDS

Description

PPE Type : *protective glove against mechanical risks*

Product MY-1505-NFXR

Article code : 209656

Glove description : 15 GAUGE RED SEAMLESS LINER, MICRO FOAM NITRILE PALM COATED.

Available sizes : 6 - 12

Pictures :



My-T-Gear®

MY-1505-NFXR 10

EN388:2016
+A1:2018



4121X



Reference standard :

Levels of performance / class of protection

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

« 0 » indicates that the glove falls below the minimum performance level for the individual hazard.

EN ISO 21420:2020

-

EN 388:2016 + A1:2018

4 1 2 1 X

At the date of the certificate, the product is in compliance with Annex XVII of REACH regulation (n° 1907/2006 and revisions)

Full description of the PPE, reference rules verified in the context of the EU-type examination and information given on the product are detailed in the manufacturer's technical file and the user instructions index 01 dated from March 2025.

NOTA : Any modification to new items of the personal protective equipment object of this EU type approval certificate or any modification of the information contained in the manufacturer technical file which served for the deliverance of the EU type approval certificate (change of address, change of company status) should be brought to the attention of the notified body in accordance with Annex V §7.2 of Regulation 2016/425. Any marking on the PPE which is not concerned by the Regulation (UE) 2016/425, is not covered by this certificate.

Issued in Lyon by
William GELAS
Certification manager



Date of first issue: 14 March 2025
Date of end of validity: 14 March 2030



In application of the Regulation 2016/425 of the European parliament and the Council of 9th March 2016 related to Personal Protective Equipment and repealing the Directive 89/686/EEC.



Accreditation n° 5-0594
Scope available on:
www.cofrac.fr

www.ctcgroupe.com

cemarking@ctcgroupe.com

CTC - 4, rue Hermann Frenkel - 69367 Lyon cedex 07 - France
Tél. : +33 (0)4 72 76 10 10 - Fax : +33 (0)4 72 76 10 00 - ctclyon@ctcgroupe.com

Comité Professionnel de Développement Économique (CPDE) Cuir Chaussure Maroquinerie Ganterie
Loi 78-654 du 22.06.1978 - Siret 77564972600160 - Code NAF 9412Z - TVA FR 88775649726

Intersafe Netherlands B.V.

MANUFACTURER'S TECHNICAL FILE TO THE PPE REGULATION 2016/425

Reference of the product	:	MY-1505-NFXR
Article code	:	209656
Technical file index	:	01
Last update	:	March 2025

IDENTIFICATION

Reference of the product :	:	MY-1505-NFXR
Article code :	:	209656
Basic Model		
Technical file index :	:	01
Last update :	:	March 2025

Manufacturer :

Intersafe Netherlands B.V.

Carrosserieweg 5, 3445 BC WOERDEN

THE NETHERLANDS

tel : +31 78 618 1400

fax :

Factory :

NANTONG QIANGSHENG NEW MATERIALS TECHNOLOGY CO., LTD.

No.118, JIALINGJIANG ROAD, RUDONG ECONOMIC DEVELOPMENT ZONE,
JIANGSU PROVINCE

CHINA

tel: 86-513-4108356

fax: 86-513-4108190

NANTONG QIANGSHENG NEW MATERIALS TECHNOLOGY CO., LTD.

YOUYI ROAD (W), JUEGANG, RUDONG JIANGSU

CHINA

tel: 86-513-4108356

fax: 86-513-4108190

NANTONG QIANGSHENG NEW MATERIALS TECHNOLOGY CO., LTD.

JINSHAJIANG ROAD, NEW INDUSTRIAL ZONE, RUDONG, JIANGSU

CHINA

tel: 86-513-84129800

fax: 86-513-84129808

NANTONG QIANGSHENG NEW MATERIALS TECHNOLOGY CO., LTD.

JINSHAJIANG ROAD, JUEGANG, RUDONG JIANGSU

CHINA

tel: 86-513-84129800

fax: 86-513-84129808

GLOVE DESCRIPTION

General glove description and intended use:

15 GAUGE RED SEAMLESS LINER, MICRO FOAM NITRILE PALM COATED.

This glove is designed against mechanical risks.

Type of coating finish : foam

Visual description (picture back and palm sides) :



Risk assessment (Essential Health and Safety Requirement. Annex II - PPE Regulation)

		Applicable	Covered by
§1	Requirements defined in the Annex II §1 are applicable to all PPE	☒	☒ Standard ☒ Instruction for use ☒ Marking
§1.4	Manufacturer's instructions and information is available	☒	☒ Standard ☒ Instruction for use ☐ Marking
§2.5	PPE which may be caught up during use	☒	☐ Standard ☒ Instruction for use ☐ Marking
§2.12	PPE bearing one or more identification markings or indicators directly or indirectly relating to health and safety	☒	☒ Standard ☒ Instruction for use ☒ Marking
§3.3	The PPE is intended to protect against mechanical injuries	☒	☒ Standard ☒ Instruction for use ☒ Marking

Glove constitution :

	Reference	Color	Material	Surfacic mass (g/m ²)	Gauges	Thickness
Palm		Black	Nitrile			0.85 - 1.50mm
		RED	Nylon	350g/m ²	15	
Back		RED	Nylon	350g/m ²	15	
Cuff		RED	Nylon/ Elastic	450g/m ²		
Binding		White/ red/ yellow/ brown/ blue/ purple/ grey/ orange/ black/ green	Polyester			

PROTECTION SCOPE

This glove meets the essential requirements of the Personal Protective Equipment Regulation 2016/425.

This glove is designed against mechanical risks.

It is a category II product.

GENERAL REQUIREMENTS

Standard EN ISO 21420 : 2020

Dexterity : 5

Available size range: 6 - 12

The hand sizing system is based on hand circumference and hand length as defined in EN ISO 21420 Annex B table B.1

SPECIFIC REQUIREMENTS AND PERFORMANCE LEVELS

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

« 0 » indicates that the glove falls below the minimum performance level for the individual hazard.

Mechanical hazard EN 388:2016 + A1:2018

Protection offered	Performance levels
Abrasion resistance	4
Blade cut resistance	1
Tear strength resistance	2
Puncture resistance	1
Cut Resistance method (EN ISO 13997)	X
Impact Protection	N/A

The levels of performance have been measured on the palm.

TEST REPORTS

Laboratory	CTC	Other
EN ISO 21420 + innocuousness	S250201590_1 S240707241_2 S221107911_1 S220804668_1 S221107909_1 S221107907_1 S221107912_1 S220804669_1 S221107906_1 S221107908_1 S221107910_1 S221107904_1	
EN 388	S250201589_1 S220703477_1 S220703478_1 S240707240_2 S220703476_1	

MARKING - PACKAGING

Information printed on the glove :

Logo of Manufacturer :

Logo 

Glove's reference : MY-1505-NFXR

Article Code : 209656

Size indicator

Pictograms related to risks against which protection is offered with performance levels

Information pictogram

Address of Manufacturer :


Date of Manufacture (month/year) and/or serial/batch number :

Date of obsolescence (month/year) if applicable:

Marking example :



Marking of packaging example :



Method of marking on the glove :

HEAT TRANSFER PRINT AND SEWN LABEL

Packaging suitable for transport:

ONE DOZEN PER BIG POLYBAG, 10 DOZEN PER CARTON

PPE subject to ageing :

The design performance can not be significantly affect by ageing when stored in appropriate conditions (humidity, temperature, clean , ventilated, light).

Cleaning instructions:

The gloves are not washable.

MEANS OF CONTROL

We make all inspection based on the acceptance sampling. Materials Conduct inspection on all incoming raw materials and accessory materials. Conduct size checking on all component parts. Conduct visual inspection on defective parts. Checking missing parts before sending to sewers. Inspected for defects, gauged for proper thickness. Quality checking on sewing in areas of appearance, sizing(based on the ENISO21420 sizing standard), weight,labelling, stitches, seaming and component positioning. After coating we will make the sizing, weight,smell,PH,chemic test and cutting ,abrasion test (based on EN388 standard) every 5 years. Finished Products perform random checking(acceptance sampling) before shipment. Quality control is performed under ISO 9001.



INSTRUCTIONS FOR USE

Intersafe Netherlands B.V.

Carrosserieweg 5, 3445 BC WOERDEN

THE NETHERLANDS

Glove reference : MY-1505-NFXR

Article code: 209656

User notice index : 01

Last update : March 2025

Glove description :

15 GAUGE RED SEAMLESS LINER, MICRO FOAM NITRILE PALM COATED.

This glove is a personal protective equipment belonging to the category II.

It meets the requirements of the PPE Regulation 2016/425 : innocuousness, comfort, solidity.

It has been subject to a UE-type Examination performed by :

C.T.C. (0075)
4, rue Hermann Frenkel
69367 LYON Cedex 07
FRANCE

The glove meets the requirements of the standard EN ISO 21420:2020 « Protective Gloves - General requirements and test methods ».

Dexterity: 5

Available size range: 6 - 12

The hand sizing system is based on hand circumference and hand length as defined in EN ISO 21420 Annex B.

Information about marking

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

« 0 » indicates that the glove falls below the minimum performance level for the individual hazard.

 The CE marking means that this product meets the requirements of the regulation 2016/425

Mechanical hazard - EN 388:2016 + A1:2018



4 1 2 1 X

Levels of performance

Abrasion resistance	4	(on 4 maxi)
Blade cut resistance	1	(on 5 maxi)
Tear resistance	2	(on 4 maxi)
Puncture resistance	1	(on 4 maxi)
Cut Resistance method (EN ISO 13997)	X	(A to F)
Impact Protection		



Read carefully the instructions for use provided with the product

Protection limit :

Users should be warned that gloves should not be worn when there is a risk of entanglement by moving parts of machines.

This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.

The protection against risks or hazards which are not mentioned in this document is not warranted.

These levels of performance are obtained from the tests done according to conditions defined by the applicable standards.

The levels of performance mentioned are only valid for new gloves, not washed, nor regenerated.

Before use, the glove shall be visually inspected for any defect or imperfections. In case of deterioration, the gloves must be scrapped (abrasion, cut, tear...).

For gloves with two or more layers the overall classification does not necessarily reflect the performance of the outermost layer.

The levels of performance against mechanical risks are only valid for the palm of the glove.

Storage and cleaning notice

Keep in its original packaging, under ordinary temperature and humidity conditions and in clean, covered and ventilated premises.

The gloves are not washable.

PPE subject to ageing :

The design performance can not be significantly affect by ageing when stored in appropriate conditions (humidity, temperature, clean , ventilated, light).

Declaration of conformity :

Available on : www.intersafe.eu

My-T-Gear®

MY-1505-NFXR 10

EN388:2016
+A1:2018



4121X



My-T-Gear®

209656 -10

Intersafe Netherlands B.V.
Carrosserieweg 5
3445 BC WOERDEN
THE NETHERLANDS
www.intersafe.eu

P.O No: XXXXXXXX
Batch No: XXX
MFG Date: MM-XXXX

MADE IN CHINA